

## INDUSTRIAL COMPONENT DATA

# DILM32-XTED11-1(RA24) 105210 Y7-105210 EATON ELECTRIC Timer module, 24VAC/DC, 0.05-1s, off-delayed

Brand: EATON - MOELLER | Manufacturer Part Number: DILM32-XTED11-1(RA24)



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | EATON - MOELLER       |
| MPN / Reference | DILM32-XTED11-1(RA24) |
| Catalog number  | Y7-105210             |
| Category        | Timer block           |
| Minimum order   | 1 Pcs                 |
| Document ID     | EO-987A6AF4EF         |
| Generated       | 2026-08-01            |

## Product Overview

Timer module, 24VAC/DC, 0.05-1s, off-delayed

DILM32-XTED11-1(RA24)

Eaton Moeller® series DILM Timer module, 24VAC/DC, 0.05-1s, off-delayed

Timer module, Off-delayed, auxiliary voltage-free, Cannot be combined with top mounting auxiliary contacts, Incl. suppressor circuits, Product range: Accessories, Time range: 0.05 - 1 s, Mounting position: As required, except suspended, Degree of Protection: IP20, Weight: 0.08 kg, For use with: DILM7 - DILM38, DILMP20, DILMP32-DILMP45, DILA, DILMF7, DILMF11, DILMF14, DILMF25, DILMF32, Standards DIN EN 61812, IEC/EN 60947, VDE 0660, UL, CSA

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

## Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM timer module Catalog Number 105210 Model Code DILM32-XTED11-1(RA24)

EAN 4015081050079 Product Length/Depth 86 mm Product Height 38 mm Product Width 45 mm Product Weight 0.073 kg

Certifications CSA Class No.: 3211-03

CE

CSA

IEC/EN 60947

IEC/EN 60947-4-1

UL 508

UL Category Control No.: NKCR

VDE 0660

UL

CSA File No.: 012528

CSA-C22.2 No. 14-05

DIN EN 61812

UL File No.: E29184 Catalog Notes Cannot be combined with top mounting auxiliary contacts Features & Functions

Fitted with: Suppressor circuits Operating mode Electronic General

Delay time 200 ms, Off-delayed

50 ms, On-delayed Lifespan, mechanical 3,000,000 Operations (AC operated)

3,000,000 Operations (DC operated) Operating frequency 360 mechanical Operations/h

3600 Operations/h Overvoltage category III Pollution degree 3 Product category Accessories Protection Finger and

back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage

(Uimp) 4000 V AC Recovery time 70 ms (after 100 % time delay) Ambient conditions, mechanical

Mounting position As required (except suspended) Shock resistance 6 g, N/C auxiliary contact, Mechanical, according to

IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

6 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C A...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM32-XTED11-1(RA24) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.