

INDUSTRIAL COMPONENT DATA

ETR2-44 262730 Y7-262730 EATON ELECTRIC Timing relay, 0.05s-100h, 24-240VAC 50/60Hz, 24-48VDC, 1W, flashing,..

Brand: EATON - MOELLER | Manufacturer Part Number: ETR2-44



Manufacturer	EATON - MOELLER
MPN / Reference	ETR2-44
Catalog number	Y7-262730
Category	Timer relay
Minimum order	1 Pcs
Document ID	EO-68A10E50A5
Generated	2026-08-06

Product Overview

Timing relay, 0.05s-100h, 24-240VAC 50/60Hz, 24-48VDC, 1W, flashing, 2 times

ETR2-44

Eaton Moeller® series ETR2 Timing relay, 0.05s-100h, 24-240VAC 50/60Hz, 24-48VDC, 1W, flashing, 2 times

ETR2 electronic timing relays, 17.5 mm wide, time range 0.05s-100h, 1 changeover contacts flashing 2 times

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Relay timers (KETR, KEMR, KESR)

Additional Product Information

General specifications

Product Name Eaton Moeller® series ETR2 Timing relay Catalog Number 262730 Model Code ETR2-44 EAN 4015082627300 Product Length/Depth 63 mm Product Height 70 mm Product Width 17.5 mm Product Weight 0.053 kg

Certifications CSA File No.: UL report valid

UL

CSA-22.2 No. 14

IEC/EN 61812-1

UL 508

CE

UL Category Control No.: NKCR, NKCR7

IEC/EN 60947-5-1

UL File No.: E29184

Certified by UL for use in Canada

CSA Class No.: 3211-03 Catalog Notes Package quantity 1 Features & Functions

Electric connection type Screw connection Functions Clock function, starting with pulse, variable

Remote operation possible

Flashing, pulse initiating

Fixed timing function

Flashing, starting with pulse, fixed time

Clock function, starting with pause, variable

Flashing, starting with pause, fixed time

Flashing, pause initiating

Pulse and pause times independently adjustable General

Degree of protection IP20 Number of contacts (change-over contacts) 1 Product category ETR2 timing relays Suitable for DIN rail (top hat rail) mounting Time range - min 0.05 s Time range - max 360000 s Type Timer relay Used with XC100, XC121, XC200 Voltage type AC/DC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Electrical rating

Mains voltage tolerance 24 - 48 V DC

24 - 240 V AC (at 50/60 Hz) Nominal current 3 A Rated operational current (Ie) 4 A at AC-15, 220 V 230 V 240 V

3 A at 230 V (NC)

3 A at 230 V (NO) Magnet system

Rated co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ETR2-44 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.