

INDUSTRIAL COMPONENT DATA

ETR2-42 262688 Y7-262688 EATON ELECTRIC Timing relay, 0.05s-100h, 24-240VAC 50/60Hz, 24-48VDC, 1W, flashing

Brand: EATON - MOELLER | Manufacturer Part Number: ETR2-42



Manufacturer	EATON - MOELLER
MPN / Reference	ETR2-42
Catalog number	Y7-262688
Category	Timer relay
Minimum order	1 Pcs
Document ID	EO-B5C3B9FE88
Generated	2026-08-06

Product Overview

Timing relay, 0.05s-100h, 24-240VAC 50/60Hz, 24-48VDC, 1W, flashing

ETR2-42

Eaton Moeller® series ETR2 Timing relay, 0.05s-100h, 24-240VAC 50/60Hz, 24-48VDC, 1W, flashing

ETR2 electronic timing relays, 17.5 mm wide, time range 0.05s-100h, 1 changeover contacts flashing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Relay timers (KETR, KEMR, KESR)

Additional Product Information

General specifications

Product Name Eaton Moeller® series ETR2 Timing relay Catalog Number 262688 Model Code ETR2-42 EAN 4015082626884 Product Length/Depth 63 mm Product Height 70 mm Product Width 17.5 mm Product Weight 0.051 kg

Certifications Certified by UL for use in Canada

UL 508

CSA File No.: UL report valid

UL

CSA-22.2 No. 14

CSA Class No.: 3211-03

IEC/EN 61812-1

UL File No.: E29184

CE

IEC/EN 60947-5-1

UL Category Control No.: NKCR, NKCR7 Features & Functions

Electric connection type Screw connection Functions Flashing, starting with pause, fixed time

Flashing, starting with pulse, fixed time

Fixed timing function

Flashing, pulse initiating

Remote operation possible General

Degree of protection IP20 Number of contacts (change-over contacts) 1 Product category ETR2 timing relays Suitable for

DIN rail (top hat rail) mounting Time range - min 0.05 s Time range - max 360000 s Type Timer relay Voltage type AC/DC

Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Electrical rating

Mains voltage tolerance 24 - 240 V AC (at 50/60 Hz)

24 - 48 V DC Nominal current 3 A Rated operational current (Ie) 3 A at 230 V (NC)

3 A at 230 V (NO)

4 A at AC-15, 220 V 230 V 240 V Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min 24 V Rated control supply voltage (Us) at AC, 50 Hz - max 240 V

Rated control supply voltage (Us) at AC, 60 Hz - min 24 V Rated control supply voltage (Us) at AC, 60 Hz - max 240 V

Rat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ETR2-42 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.