

INDUSTRIAL COMPONENT DATA

ETR4-69-A 031891 Y7-31891 EATON ELECTRIC Timing relay, 1W, 0.05s-100h, multi-function, 24-240VAC/DC

Brand: EATON - MOELLER | Manufacturer Part Number: ETR4-69-A



Manufacturer	EATON - MOELLER
MPN / Reference	ETR4-69-A
Catalog number	Y7-31891
Category	Timer relay
Minimum order	1 Pcs
Document ID	EO-508B6C84BC
Generated	2026-08-02

Product Overview

Timing relay, 1W, 0.05s-100h, multi-function, 24-240VAC/DC

Timer Relay 1 W 0.05 s-100 h Multi-Function 24-240 V AC/DC

Eaton Moeller® series ETR4 Timing relay, 1W, 0.05s-100h, multi-function, 24-240VAC/DC

Electronic timing relay according to IEC/EN 61812-1, VDE 0435, 22.5 mm wide, time range 0.05s-100h, mechanical lifespan 30 * 10⁶, DIN top-hat rail mounting, any required mounting position, 24-240VAC/DC, multi-functional, industry form factor

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Relay timers (KETR, KEMR, KESR)
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series ETR4 Timing relay Catalog Number 031891 Model Code ETR4-69-A EAN

4015080318910 Product Length/Depth 103 mm Product Height 83 mm Product Width 23 mm Product Weight 0.11 kg

Certifications CSA File No.: 012528

VDE 0435

UL 508

CSA-22.2 No. 14

IEC/EN 61000-4-3

Standard IEC/EN 61812

IEC/EN 60947-5-1

IEC/EN 61000-4-2

UL File No.: E29184

UL

UL Category Control No.: NKCR

CE

CSA

CSA Class No.: 3211-03

IEC/EN 61812-1 Features & Functions

Electric connection type Screw connection Functions Flashing, pulse initiating

On- and Off-delayed

Pulse generating

Adjustable timing function

Outputs, reversible delayed/undelayed

Off-delayed

Pulse forming

Delay on de-energization

Multi-functional

Fleeting contact on energization

Clock function, starting with pause, variable

Clock function, starting with pulse, variable

On-delayed

Delay-on energization

Flashing, starting with pulse, fixed time

Fleeting contact on de-energization

Flashing, starting with pause, fixed time

Pulse shaping General

Degree of protection IP20

Terminals: IP20 Lifespan, mechanical 30,000,000 Operations (DC operated)

30,000,000 Operations (AC operated) Mounting position As required Number of contacts (change-over contacts) 1

Overvoltage category III Pollution degree 2 Product category ETR4 timing relays Rated impulse withstand voltage (Uimp)
4000 V AC

6000 V AC Shock resistance 4 g, Make contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms
Suited...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ETR4-69-A with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.