

INDUSTRIAL COMPONENT DATA

DILET11-30-A 048878 EATON ELECTRIC XTMT6A30S11B

DILET 11-30-A multifunction timer

Brand: EATON - MOELLER | Manufacturer Part Number: DILET11-30-A



Manufacturer	EATON - MOELLER
MPN / Reference	DILET11-30-A
Catalog number	048878
Category	Timer relay
Minimum order	1 Pcs
Document ID	EO-C82FDDD6FC
Generated	2026-08-05

Product Overview

XTMT6A30S11B DILET 11-30-A multifunction timer

Electronic timing relay according to IEC/EN 61812-1, VDE 0435, 45 mm wide, 24-240VAC/DC, time range 1.5-30s, on-delayed, ideal for combination with contactors

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

Program Delivery Product range DILET timing relays

The basic function of Relay timer

The function In retarded

Sets the timing function

Number of switching contacts 1

Time Range 1.5 - 30 s

Time Range 1.5 - 30 s

Rated Operating Current

AC-11

230 V land One 3

380 V 400 V 415 V land One 3

AC-15

220 V 230 V 240 V land One 3

Voltage range of ULN V 24 - 240 VAC, 50/60 Hz
24 - 240 V DC
Wide mm 45
Terminal of the brand according to EN 50042
General
Standards The IEC/EN 61812 standard
VDE 0435
Life expectancy, mechanics
AC operated The operations of x 106 30
DC operated The operations of x 106 30
Climatic correction Moist, Constant Heat, IEC 60068-2-78
Moist, cyclic heat, IEC 60068-2-30
Ambient Temperature
Open °C -20 - +60
Closed °C - 20 - + 45
Mounting position As required
Shock Resistance Mechanics (IEC/EN 60068-2-27)
Sinusoidal half shock, 20 ms g
Make contact g 4
Degree of protection
Terminals IP20
Weight kg 0.09
Capacity terminal mm²
Solid mm² 1 x (0.75 - 2.5)
2 x (0.75 - 2.5)
Flexible with cap mm² 1 x (0.75 - 1.5)
2 x (0.75 - 1.5)
Solid or braided AWG 1 x (18 - 14)
Contacts
Rated Supported Pulse Voltage U_{imp} V AC 6000
Overvoltage category/degree of contamination III/2
Rated insulation voltage U_i V AC 600
Rated Operating Voltage U_{and} V AC 440
Safety insulation according to EN 61140
between coil and auxiliary contacts V AC 250
between auxiliary contacts V AC 250
The manufacturing capacity of
Nah, no way One 48
AC-15 cos φ = 0.3 220 V One 50
DC-11 L/R 40 ms x land 1.1
Breaking cap...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILET11-30-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.