

INDUSTRIAL COMPONENT DATA

ZRTAK/W 110747 Y7-110747 EATON ELECTRIC Timing relay, clock generator, 1 changeover contacts

Brand: EATON - MOELLER | Manufacturer Part Number: ZRTAK/W



Manufacturer	EATON - MOELLER
MPN / Reference	ZRTAK/W
Catalog number	Y7-110747
Category	Timer relay
Minimum order	1 Pcs
Document ID	EO-AB7A55B9CC
Generated	2026-08-03

Product Overview

Timing relay, clock generator, 1 changeover contacts

ZRTAK/W

Eaton Distribution parts. Timing relay, clock generator, 1 changeover contacts

Timing relay single function, pulse generator (2 times adjustable), 2 functions, 7 time end ranges, supply voltage 24-240VAC/DC, 1 changeover contacts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 110747 Model Code ZRTAK/W EAN 4015081102853 Product Length/Depth 65 mm Product Height 87 mm Product Width 17.5 mm Product Weight 0.067 kg Compliances RoHS conform Product specifications

Electric connection type Screw connection Ambient operating temperature - max 55 °C Ambient operating temperature - min -25 °C Nominal current 8 A Degree of protection IP20 Functions Clock function, starting with pulse, variable Clock function, starting with pause, variable Voltage type AC/DC Suitable for Front mounting

DIN rail (top hat rail) mounting Number of outputs (delayed, change-over contact) 1 Number of outputs (delayed, normally closed contact) 0 Number of outputs (delayed, normally open contact) 0 Number of outputs (undelayed, change-over contact) 0 Number of outputs (undelayed, normally closed contact) 0 Number of outputs (undelayed, normally open contact) 0 Rated control supply voltage (Us) at AC, 50 Hz - max 240 V Rated control supply voltage (Us) at AC, 50 Hz - min 24 V

Rated control supply voltage (Us) at AC, 60 Hz - max 240 V Rated control supply voltage (Us) at AC, 60 Hz - min 24 V
Rated control supply voltage (Us) at DC - max 240 V Rated control supply voltage (Us) at DC - min 24 V Static heat
dissipation, non-current-dependent 1.5 W Time range - max 360000 s Time range - min 0.05 s Starting current - max 8 A
Voltage type of operating voltage AC/DC Operating voltage at AC, 50 Hz - min 24 V Operating...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ZRTAK/W with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.