

INDUSTRIAL COMPONENT DATA

ZRMF1/W 110406 Y7-110406 EATON ELECTRIC Timing relay multi-function, 7 functions, 1 changeover contacts

Brand: EATON - MOELLER | Manufacturer Part Number: ZRMF1/W



Manufacturer	EATON - MOELLER
MPN / Reference	ZRMF1/W
Catalog number	Y7-110406
Category	Timer relay
Minimum order	1 Pcs
Document ID	EO-ABB02FC692
Generated	2026-08-01

Product Overview

Timing relay multi-function, 7 functions, 1 changeover contacts

ZRMF1/W

Eaton Distribution parts. Timing relay multi-function, 7 functions, 1 changeover contacts, W

Timing relay multi-function, 7 functions, 7 time end ranges, resilient control contact, supply voltage 24-240VAC/DC, 1 changeover contacts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 110406 Model Code ZRMF1/W EAN 4015081099467 Product Length/Depth 65 mm Product Height 87 mm Product Width 17.5 mm Product Weight 0.069 kg Compliances RoHS conform Product specifications

Electric connection type Screw connection Ambient operating temperature - max 55 °C Ambient operating temperature - min -25 °C Nominal current 8 A Degree of protection IP20 Functions Delay-on energization

Floating contact on de-energization

Delay on de-energization

Floating contact on energization

Pulse shaping Voltage type AC/DC Suitable for DIN rail (top hat rail) mounting

Front mounting Number of outputs (delayed, change-over contact) 1 Number of outputs (delayed, normally closed contact)

0 Number of outputs (delayed, normally open contact) 0 Number of outputs (undelayed, change-over contact) 0 Number of outputs (undelayed, normally closed contact) 0 Number of outputs (undelayed, normally open contact) 0 Rated control supply voltage (Us) at AC, 50 Hz - max 240 V Rated control supply voltage (Us) at AC, 50 Hz - min 24 V Rated control supply voltage (Us) at AC, 60 Hz - max 240 V Rated control supply voltage (Us) at AC, 60 Hz - min 24 V Rated control supply voltage (Us) at DC - max 240 V Rated control supply voltage (Us) at DC - min 24 V Static heat dissipation, non-current-dependent 1.5 W Time range - max 360000 s Time range - min 0.05 s Starting current - max 8 A Voltage type of operating voltage AC/DC Operating vol...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ZRMF1/W with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.