

INDUSTRIAL COMPONENT DATA

TLE 101064 Y7-101064 EATON ELECTRIC Timing relay, stairwell time switch, impulse relay (4 Fct No.)

Brand: EATON - MOELLER | Manufacturer Part Number: TLE



Manufacturer	EATON - MOELLER
MPN / Reference	TLE
Catalog number	Y7-101064
Category	Timer relay
Minimum order	2 Pcs
Document ID	EO-A0AFB8FFBB
Generated	2026-08-03

Product Overview

Timing relay, stairwell time switch, impulse relay (4 Fct No.)

TLE

Eaton Distribution parts. Timing relay, stairwell time switch, impulse relay (4 Fct No.)

Timing relays, stairwell time switch, impulse relay, multi-function, 4 functions, supply voltage 230VAC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 101064 Model Code TLE EAN 4015081011698 Product Length/Depth 65 mm Product Height 87 mm Product Width 17.5 mm Product Weight 0.061 kg Compliances RoHS conform Product specifications

Electric connection type Screw connection Ambient operating temperature - max 55 °C Ambient operating temperature - min -25 °C Nominal current 16 A Degree of protection IP20 Functions Delay on de-energization Voltage type AC Suitable for Front mounting

DIN rail (top hat rail) mounting Number of outputs (delayed, change-over contact) 0 Number of outputs (delayed, normally closed contact) 0 Number of outputs (delayed, normally open contact) 1 Number of outputs (undelayed, change-over contact) 0 Number of outputs (undelayed, normally closed contact) 0 Number of outputs (undelayed, normally open contact) 0 Rated control supply voltage (Us) at AC, 50 Hz - max 230 V Rated control supply voltage (Us) at AC, 50 Hz - min 230 V Rated control supply voltage (Us) at AC, 60 Hz - max 230 V Rated control supply voltage (Us) at AC, 60 Hz - min 230 V

Rated control supply voltage (Us) at DC - max 0 V Rated control supply voltage (Us) at DC - min 0 V Static heat dissipation, non-current-dependent 1 W Time range - max 720 s Time range - min 30 s Starting current - max 80 A Voltage type of operating voltage AC Operating voltage at AC, 50 Hz - min 230 V Operating voltage at AC, 60 Hz - min 230 V ETIM for 101064 Relays (EC001439)

Feature Name

F...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TLE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.