

INDUSTRIAL COMPONENT DATA

TLK 101066 Y7-101066 EATON ELECTRIC Timing relay, stairwell time switch, impulse relay (6 Fct No.)

Brand: EATON - MOELLER | Manufacturer Part Number: TLK



Manufacturer	EATON - MOELLER
MPN / Reference	TLK
Catalog number	Y7-101066
Category	Timer relay
Minimum order	2 Pcs
Document ID	EO-03C1BB8CE7
Generated	2026-08-04

Product Overview

Timing relay, stairwell time switch, impulse relay (6 Fct No.)

TLK

Timing relays, stairwell time switch, impulse relay, multi-function, 6 functions, supply voltage 230VAC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 101066 Model Code TLK EAN 4015081011711 Product Length/Depth 65 mm Product Height 87 mm Product Width 17.5 mm Product Weight 0.07 kg Compliances RoHS conform Product specifications

Electric connection type Screw connection Ambient operating temperature - max 55 °C Ambient operating temperature - min -25 °C Nominal current 16 A Degree of protection IP20 Functions Delay on de-energization Voltage type AC Suitable for DIN rail (top hat rail) mounting

Front mounting Number of outputs (delayed, change-over contact) 0 Number of outputs (delayed, normally closed contact) 0 Number of outputs (delayed, normally open contact) 1 Number of outputs (undelayed, change-over contact) 0 Number of outputs (undelayed, normally closed contact) 0 Number of outputs (undelayed, normally open contact) 0 Rated control supply voltage (Us) at AC, 50 Hz - max 230 V Rated control supply voltage (Us) at AC, 50 Hz - min 230 V Rated control supply voltage (Us) at AC, 60 Hz - max 230 V Rated control supply voltage (Us) at AC, 60 Hz - min 230 V Rated control supply voltage (Us) at DC - max 0 V Rated control supply voltage (Us) at DC - min 0 V Static heat dissipation,

non-current-dependent 1 W Time range - max 720 s Time range - min 30 s Starting current - max 80 A Voltage type of operating voltage AC Operating voltage at AC, 50 Hz - min 230 V Operating voltage at AC, 60 Hz - min 230 V

ETIM for 101066 Relays (EC001439)

Feature Name

Fe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TLK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.