

INDUSTRIAL COMPONENT DATA

TLM750 EATON ELECTRIC Fuse-link, low voltage, 750 A, AC 660 V, DC 350 V, BS88/C3, 83 x 210 mm, gL/gG, BS

Brand: EATON - MOELLER | Manufacturer Part Number: TLM750



Manufacturer	EATON - MOELLER
MPN / Reference	TLM750
Catalog number	10000
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-F89957D925
Generated	2026-08-06

Product Overview

750A 660V AC / 350V DC INDUSTRIAL FUSE

Fuse-link, low voltage, 750 A, AC 660 V, DC 350 V, BS88/C3, 83 x 210 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 750 A, AC 660 V, DC 350 V, BS88/C3, 83 x 210 mm, gL/gG, BS, centre-bolted tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number TLM750 EAN 5996516026533

Product Length/Depth 210 mm Product Height 83 mm Product Width 83 mm Product Weight 0.015 g Compliances CE

Marked

RoHS Compliant Certifications BS88

IEC 60269

EAC Electrical data

Amperage Rating 750 A Voltage rating 660 V Voltage type AC/DC Breaking capacity 80 kA Class Class gG/gL Product specifications

Fuse type TLM Fitted with: Centre bolted tags Construction BS88/C3

ETIM for TLM750 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

C3

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

660 V

Rated voltage DC (EF012281)

350 V

Rated current (EF000227)

750 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Mounting holes (EF021553)

M10

Centre-to-centre distance of connections (EF021151)

183.8 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TLM750 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.