

INDUSTRIAL COMPONENT DATA

TM-7-SOND-ERSTBESTELLUNG/E 208273 Y7-208273 EATON ELECTRIC TM-7-SOND-ERSTBESTELLUNG/E

Brand: EATON - MOELLER | Manufacturer Part Number: TM-7-SOND-ERSTBESTELLUNG/E



Manufacturer	EATON - MOELLER
MPN / Reference	TM-7-SOND-ERSTBESTELLUNG/E
Catalog number	Y7-208273
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-7A2F417CD8
Generated	2026-08-05

Product Overview

TM-7-SOND-ERSTBESTELLUNG/E

Non-standard switch, TM, 10 A, flush mounting, 7 contact unit(s), customized version according to form, TM mini rotary switches, ordering for the first time

Non-standard switch, Product range: Non-standard switch, Standards: IEC/EN 60947, VDE 0660, Control switch as per IEC/EN 60947-5-1, Auxiliary switch as per IEC/EN 60947-5-1, Part group reference: TM, customized version according to form, TM mini rotary switches, ordering for the first time, Degree of Protection: Front IP65, Design: flush mounting, 7 contact unit(s), Rated uninterrupted current: $I_u = 10$ A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Non-standard switch, TM, 10 A, flush mounting, 7 contact unit(s), customized version according to form, TM mini rotary switches, ordering for the first timeNon-standard switch, Product range: Non-standard switch, Standards: IEC/EN 60947, VDE 0660, Control switch as per IEC/EN 60947-5-1, Auxiliary switch as per IEC/EN 60947-5-1, Part group reference: TM, customized version according to form, TM mini rotary switches, ordering for the first time, Degree of Protection: Front IP65, Design: flush mounting, 7 contact unit(s), Rated uninterrupted current: $I_u = 10$ A

Delivery program
Product rangeNon-standard switchPart group referenceTMNotescustomized version according to formNon-standard orderTM mini rotary switches, ordering for the first timeDegree of ProtectionFront IP65Designflush mountingMotor rating AC-23A, 50 - 60 Hz [P]400 V [P]3 kWRated uninterrupted current [I_u]10 ANote on rated uninterrupted current I_u Rated uninterrupted current I_{uis} specified for max. cross-section.Number of contact units7 contact unit(s)Design verification as per

IEC/EN 61439

Datos técnicos para la verificación del diseñoIntensidad asignada de empleo para disipación térmica específica [In]10
ADisipación térmica por polo, en función de la intensidad [Pvid]0.15 WDisipación térmica del equipo, en función de la
intensidad [Pvid]0 WDisipación térmica estática, en función de la intensidad [Pvs]0 WCapacidad de disipación térmica
[Pdiss]0 WTemperatura ambiente mínima de funcionamiento-25 °CTemperatura ambiente má...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TM-7-SOND-ERSTBESTELLUNG/E with the required quantity to info@electricaonline.com or
use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.