

INDUSTRIAL COMPONENT DATA

TM-8-SOND*/E 907754 Y7-907754 EATON ELECTRIC

Non-standard switch, TM, 10 A, flush mounting, 8 contact unit(s)

Brand: EATON - MOELLER | Manufacturer Part Number: TM-8-SOND*/E



Manufacturer	EATON - MOELLER
MPN / Reference	TM-8-SOND*/E
Catalog number	Y7-907754
Category	Control switch
Minimum order	10 Pcs
Document ID	EO-DF976BFE42
Generated	2026-08-05

Product Overview

Non-standard switch, TM, 10 A, flush mounting, 8 contact unit(s)

TM-8-SOND*/E

Non-standard switch, Product range: Non-standard switch, Standards: IEC/EN 60947, VDE 0660, Control switch as per IEC/EN 60947-5-1, Auxiliary switch as per IEC/EN 60947-5-1, Part group reference: TM, customized version according to form, mini rotary switch TM, SOND reorder, Degree of Protection: Front IP65, Design: flush mounting, 8 contact unit(s), Rated uninterrupted current: $I_u = 10$ A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Non-standard switch, TM, 10 A, flush mounting, 8 contact unit(s)Non-standard switch, Product range: Non-standard switch, Standards: IEC/EN 60947, VDE 0660, Control switch as per IEC/EN 60947-5-1, Auxiliary switch as per IEC/EN 60947-5-1, Part group reference: TM, customized version according to form, mini rotary switch TM, SOND reorder, Degree of Protection: Front IP65, Design: flush mounting, 8 contact unit(s), Rated uninterrupted current: $I_u = 10$ A

General specificationsProduct nameEaton Moeller® series TM Non-standard switchPart no.TM-8-SOND*/EProduct

Length/Depth146 millimetreProduct height30 millimetreProduct width30 millimetreProduct weight0.1

kilogramCertificationsIEC/EN 60947

IEC/EN 60947-5-1

VDE 0660Product TradenameTMProduct TypeNon-standard switchProduct Sub TypeNoneCatalog NotesCustomized version according to form
mini rotary switch TM, SOND reorderFeatures & FunctionsNumber of polesZero-poleGeneral informationDegree of protection (front side)IP65
NEMA 12Lifespan, mechanical1,000,000 OperationsMounting methodFlush mountingMounting positionAs requiredNumber of contact units8Operating frequency1200 Operations/hOvervoltage categoryIIIPollution degree3Product categoryNon-standard switchRated impulse withstand voltage (Uimp)4000 V ACSuitable forFront mountingClimatic environmental conditionsAmbient operating temperature - min-25 °CAmbient operating temperature - max50 °CClimatic proofingDamp heat, cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78Terminal...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TM-8-SOND*/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.