

INDUSTRIAL COMPONENT DATA

ZP-IHK 286052 Y7-286052 EATON ELECTRIC Auxiliary contact, for PLS, postal Code, PKNM, ZP-A40...-ASA...IHK.....

Brand: EATON - MOELLER | Manufacturer Part Number: ZP-IHK



Manufacturer	EATON - MOELLER
MPN / Reference	ZP-IHK
Catalog number	Y7-286052
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-C5D183F3E2
Generated	2026-08-04

Product Overview

Auxiliary contact, for PLS, postal Code, PKNM, ZP-A40...-ASA...IHK...WHK, Z-MS, 1N/O+1N/C, 0.5HP
ZP-IHK

Eaton Distribution parts. Auxiliary contact, for PLS, postal Code, PKNM, ZP-A40...-ASA...IHK...WHK, Z-MS, 1N/O+1N/C, 0.5HP

PLS, postal Code, PKNM, ZP-A40...-ASA...IHK...WHK, Z-MS, + 1N/O for 1N/C, 0.5auxiliary contacts, for PLS, postal Code, PKNM, ZP-A40...-ASA...IHK...WHK, Z-MS, 1N/O+1N/C, 0.5 SU auxiliary contact, 1N/O+1N/CSU

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Others and Accessories
--------------	---

Additional Product Information

General specifications

Product Name Eaton Distribution parts

Catalog Number 286052

Model Code ZP-IHK

EAN 4015082860523

Product Length/Depth 80 mm

Product Height 75 mm

Product Width 8.8 mm

Product Weight 0.043 kg

Compliances RoHS conform

Certifications EN45545-2

IEC 61373

Product specifications

Used with Auxiliary contacts

Accessory for combined residual current/power circuit breaker

Accessory for miniature circuit breaker

Accessory

Accessory/spare part type Auxiliary contacts

Mounting method For fitting on left to: LS, FI/LS

Additional equipment required Auxiliary switch

Ambient operating temperature - max 55 °C

Ambient operating temperature - min -5 °C

Assembly width 0.5 TE

Number of contacts (change-over contacts) 0

Number of contacts (normally closed contacts) 1

Number of contacts (normally open contacts) 1

Number of poles at main contact unit - max 2

Number of switches (fault signal) 0

Voltage type AC

Functions Auxiliary switch

Device fitting Universal

Type Accessory

Accessory for combined residual current/power circuit breaker

Accessory for miniature circuit breaker

Application Switchgear for industrial and advanced commercial applications

Rated operational voltage (Ue) - max 230 V

Rated switch current 3 A

Suitable for current of main contact unit - max 6 A

ETIM for 286052 Modular devices for distribution board/surface mounting (EC001286)

Feature Name

Feature Value

Device fitting (EF007826)

Universal

Function (EF000030)

Auxiliary switch

Width in number of modular spacin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ZP-IHK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.