

INDUSTRIAL COMPONENT DATA

ZP-NHK 248437 Y7-248437 EATON ELECTRIC Auxiliary contact, for PLS, postal Code, PKNM, ZP-A40, ZP-ASA, Z-MS,

..

Brand: EATON - MOELLER | Manufacturer Part Number: ZP-NHK



Manufacturer	EATON - MOELLER
MPN / Reference	ZP-NHK
Catalog number	Y7-248437
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-70DAA4DC8C
Generated	2026-08-05

Product Overview

Auxiliary contact, for PLS, postal Code, PKNM, ZP-A40, ZP-ASA, Z-MS, 2W, 0.5HP

ZP-NHK

Eaton Distribution parts. Auxiliary contact, for PLS, postal Code, PKNM, ZP-A40, ZP-ASA, Z-MS, 2W, 0.5HP

PLS, postal Code, PKNM, ZP-A40, ZP-ASA, Z-MS, for 2W, 0.5auxiliary contacts, for PLS, postal Code, PKNM, ZP-A40, ZP-ASA, Z-MS, 2W, 0.5 SU auxiliary contact, 2WSU

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 248437 Model Code ZP-NHK EAN 4015082484378 Product Length/Depth 80 mm Product Height 75 mm Product Width 8.8 mm Product Weight 0.044 kg Compliances RoHS conform Certifications UL Listed EN45545-2

IEC 61373 Product specifications

Type Application Switchgear for industrial and advanced commercial applications Accessory/spare part type Tripping signal contacts Used with Auxiliary contacts

Accessory

Accessory for miniature circuit breaker

Accessory for combined residual current/power circuit breaker Mounting method For fitting on left to: LS, FI/LS Additional equipment required Signaling switch Ambient operating temperature - max 55 °C Ambient operating temperature - min -5 °C

Assembly width 0.5 TE Number of contacts (change-over contacts) 2 Number of contacts (normally closed contacts) 0

Number of contacts (normally open contacts) 0 Number of poles at main contact unit - max 2 Number of switches (fault signal) 0 Voltage type AC Functions Auxiliary switch Device fitting Universal Rated operational voltage (Ue) - max 250 V

Rated switch current 4 A Suitable for current of main contact unit - max 4 A

ETIM for 248437 Modular devices for distribution board/surface mounting (EC001286)

Feature Name

Feature Value

Device fitting (EF007826)

Universal

Function (EF000030)

Auxiliary switch

Width in number of modular spacings (EF002950)

0.5

Number of contacts as normally open contact (EF008256)

0

Number of contacts as...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ZP-NHK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.