

INDUSTRIAL COMPONENT DATA

K3DR/P 1818096 Y8-1818096 EATON ELECTRIC Toggle, 10mm, door installation, red/yellow, padlock

Brand: EATON - MOELLER | Manufacturer Part Number: K3DR/P



Manufacturer	EATON - MOELLER
MPN / Reference	K3DR/P
Catalog number	Y8-1818096
Category	Printed circuit board connector
Minimum order	1 unit
Document ID	EO-7BC918DF19
Generated	2026-08-05

Product Overview

Toggle, 10mm, door installation, red/yellow, padlock

K3DR/P

Toggle, Basic function: Rotary handles, Complete handle with door coupling, Shaft diameter: 10 x 10, For use with: DMVS160N, DMV250N, DMV400N, QSA160N, QSA200N, QSA250N, QSA315N, QSA400N, For use with: Door build in installation, Information about equipment supplied: with padlock, red/yellow, Switching angle: 90 °

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
With restart blockage (EF004054)	No
With key lock (EF026057)	No
Padlock locking (EF001163)	No
Colour (EF000007)	Red
Suitable for emergency stop (EF001433)	No
With extension shaft (EF001434)	No
Suitable for power circuit breaker (EF005863)	Yes
Suitable for switch disconnecter (EF007252)	Yes
Degree of protection (NEMA) (EF011959)	Other

Classification & Catalog Path

Catalog path	EATON - MOELLER > DUMECO Switch-Disconnectors
--------------	---

Additional Product Information

General specifications

Product Name Eaton K3 Accessory Toggle Catalog Number 1818096 Model Code K3DR/P EAN 8711426423657 Product Length/Depth 260 mm Product Height 80 mm Product Width 135 mm Product Weight 0.3 kg Compliances CE Features & Functions

Color Red Features Lockable General

Accessories Padlock included with supplied equipment. Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Degree of protection NEMA Other Shaft diameter 10 x 10 mm Suitable for Power circuit breaker Switch disconnecter Switching angle 90 ° Type Complete rotary handle with door coupling Design verification Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance 0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / K3DR/P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.