

INDUSTRIAL COMPONENT DATA

K4DR/P 1818051 Y8-1818051 EATON ELECTRIC Toggle, 12mm, door installation, red/yellow, padlock

Brand: EATON - MOELLER | Manufacturer Part Number: K4DR/P



Manufacturer	EATON - MOELLER
MPN / Reference	K4DR/P
Catalog number	Y8-1818051
Category	Handle for power circuit breaker
Minimum order	1 Pcs
Document ID	EO-951AC888F6
Generated	2026-08-03

Product Overview

Toggle, 12mm, door installation, red/yellow, padlock

K4DR/P

Toggle, Basic function: Rotary handles, Complete handle with door coupling, Shaft diameter: 12 x 12, For use with: QSA400, QSA630, QSA800, For use with: Door build in installation, Information about equipment supplied: with padlock, red/yellow, Switching angle: 90 °

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > DUMECO Switch-Disconnectors

Additional Product Information

Toggle, 12mm, door installation, red/yellow, padlockToggle, Basic function: Rotary handles, Complete handle with door coupling, Shaft diameter: 12 x 12, For use with: QSA400, QSA630, QSA800, For use with: Door build in installation, Information about equipment supplied: with padlock, red/yellow, Switching angle: 90 °

General specificationsProduct nameEaton K4 Accessory TogglePart no.K4DR/PEAN8711426104792Product Length/Depth330 millimetreProduct height105 millimetreProduct width200 millimetreProduct weight0.7

kilogramCompliancesCEProduct TradenameK4Product TypeAccessoryProduct Sub TypeToggleFeatures & FunctionsColorRedFeaturesLockableGeneral informationAccessoriesPadlock included with supplied equipment.Ambient operating temperature - min-25 °CAmbient operating temperature - max55 °CDegree of protectionNEMA OtherShaft diameter12 x 12 mmSuitable forPower circuit breaker

Switch disconnectorSwitching angle90 °TypeComplete rotary handle with door couplingDesign verificationEquipment heat dissipation, current-dependent Pvid0 WHeat dissipation capacity Pdisso WHeat dissipation per pole, current-dependent

Pvid0 WRated operational current for specified heat dissipation (In)0 AStatic heat dissipation, non-current-dependent Pvs0 W10.2.2 Corrosion resistanceMeets the product standard's requirements.10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2.3.2 Verification of resistance of insulating materials to normal heatMeets the product....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / K4DR/P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.