

INDUSTRIAL COMPONENT DATA

K5CB 1818025 Y8-1818025 EATON ELECTRIC Toggle, 14mm, for mounting shroud, blue

Brand: EATON - MOELLER | Manufacturer Part Number: K5CB



Manufacturer	EATON - MOELLER
MPN / Reference	K5CB
Catalog number	Y8-1818025
Category	Printed circuit board connector
Minimum order	1 unit
Document ID	EO-FECD0C41A4
Generated	2026-08-05

Product Overview

Toggle, 14mm, for mounting shroud, blue
K5CB

Toggle, Basic function: Rotary handles, Handle mounted directly on shaft, Shaft diameter: 14 x 14, For use with: DMV630N, DMV1000N, For use with: Hinged cover mounting, Switching angle: 90 °

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
With restart blockage (EF004054)	No
With key lock (EF026057)	No
Padlock locking (EF001163)	No
Colour (EF000007)	Other
Suitable for emergency stop (EF001433)	No
With extension shaft (EF001434)	No
Suitable for power circuit breaker (EF005863)	Yes
Suitable for switch disconnecter (EF007252)	Yes
Degree of protection (NEMA) (EF011959)	Other

Classification & Catalog Path

Catalog path	EATON - MOELLER > DUMECO Switch-Disconnectors
--------------	---

Additional Product Information

Toggle, 14mm, for mounting shroud, blueToggle, Basic function: Rotary handles, Handle mounted directly on shaft, Shaft diameter: 14 x 14, For use with: DMV630N, DMV1000N, For use with: Hinged cover mounting, Switching angle: 90 °
General specificationsProduct nameEaton K5 Accessory TogglePart no.K5CBEAN8711426634459Product Length/Depth370 millimetreProduct height100 millimetreProduct width190 millimetreProduct weight0.48 kilogramCompliancesCEProduct TradenameK5Product TypeAccessoryProduct Sub TypeToggleFeatures & FunctionsColorOtherGeneral informationAccessory/spare part typeAccessoryDegree of protectionNEMA OtherMounting positionHandle mounted directly on shaftShaft diameter14 x 14 mmSuitable forSwitch disconnector Power circuit breakerSwitching angle90 °TypeRotary handleClimatic environmental conditionsAmbient operating temperature - min-25 °CAmbient operating temperature - max55 °CDesign verificationEquipment heat dissipation, current-dependent Pvid0 WHeat dissipation capacity Pdisso WHeat dissipation per pole, current-dependent Pvid0 WRated operational current for specified heat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / K5CB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.