

INDUSTRIAL COMPONENT DATA

XV-152-D6-10TVR-10 150609 Y7-150609 EATON ELECTRIC

Touch panel, 24 V DC, 10.4z, TFTcolor, ethernet, RS232, R..

Brand: EATON - MOELLER | Manufacturer Part Number: XV-152-D6-10TVR-10



Manufacturer	EATON - MOELLER
MPN / Reference	XV-152-D6-10TVR-10
Catalog number	Y7-150609
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-F2E024209C
Generated	2026-08-06

Product Overview

Touch panel, 24 V DC, 10.4z, TFTcolor, ethernet, RS232, RS485, CAN, (PLC)

XV-152-D6-10TVR-10

User interface, XV-152, Product range: XV150 10.4z, Function: HMI-PLC (PLC retrofitted by user), Common features of the model series: Ethernet interface, USB device, USB Host, Slot for SD card, UL508, cUL approvals, Display - Type: Color display, TFT, Touch-technology: Resistive-Touch, Number of colors: 64 k Colors, Resolution: VGA, 640 x 480 Pixel, Portrait format: yes, Screen diagonal: 10.4 Inch, Metal enclosure and front plate, Operating system: Windows CE 5.0 (license incl.), PLC-license: Can be fitted by user with article no. 142581 LIC-PLC-MXP-COMPACT, License certificates for onboard interfaces: Not required , built-in interfaces: 1 x Ethernet 10/100 Mbps, 1 x RS232, 1 x RS485, 1 x USB host 2.0, 1 x USB device, 1 x CANopen®/easyNet, Front type: Standard front with standard membrane (fully enclosed), Utilization: Flush mounting, Slots: for SD card: 1, Memory card automation: Optionally with SD card -> article no. 139807, Pluggable communication cards (optional): no, Touch sensor: Glass with film, Heat dissipation: 14.5 W, Degree of protection (IEC/EN 60529, EN50178, VBG 4): IP65 (at front), IP20 (at rear), Enclosure Type 4X (Indoor use only)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > HMI Touch Terminals
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton XV-152 Touch panel Catalog Number 150609 Model Code XV-152-D6-10TVR-10 EAN 7640130097193 Product Length/Depth 345 mm Product Height 54 mm Product Width 260 mm Product Weight 2.95 kg Certifications ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x)

EN 60950
IEC/EN 61000-6-3
CSA Class No.: none
EN 50178
UL
IEC/EN 61000-6-4
IEC/EN 61241-0 (ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x)
UL 508
UL File No.: E205091
CUL508
UL508
CSA File No.: UL report applies to both US and Canada
IEC/EN 61000-6-2
IEC/EN 61131-2
IEC/EN 61131-2, CE
Security:
UL Category Control No.: NRAQ
IEC/EN 60079-0 (ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x)
Certified by UL for use in Canada
CULus
UL 60950
DNV GL
IEC/EN 60950
IEC/EN 61241-1 (ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x) Features & Functions
Enclosure material Metal, anodized Features Slot for SD card
Overload proof
Fanless CPU and system cooling, natural convection-based passive cooling
UL508, cUL approvals
Portrait format
Ethernet interface
USB device
USB Host Fitted with: Alpha numeric keyboard
1 x USB device (built-in interface)
1 x CANopen®/easyNet (built-in interfaces)
1 x RS485 (built-in interface)
Message indication
1 x RS232 (built-in interface)
Numeric keyboard
SW interfaces
Message system (incl. buffer and confirmation)
1 x USB host 2.0 (built-in interface)
Recipes
Printer output
Color display
1 x Ethernet 10/100 Mbps (b...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-152-D6-10TVR-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.