

INDUSTRIAL COMPONENT DATA

XV-152-D8-10TVRC-10 150612 Y7-150612 EATON ELECTRIC

Touch panel, 24 V DC, 10.4z, TFTcolor, ethernet, RS232, ..

Brand: EATON - MOELLER | Manufacturer Part Number: XV-152-D8-10TVRC-10



Manufacturer	EATON - MOELLER
MPN / Reference	XV-152-D8-10TVRC-10
Catalog number	Y7-150612
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-99925BC43A
Generated	2026-08-05

Product Overview

Touch panel, 24 V DC, 10.4z, TFTcolor, ethernet, RS232, RS485, profibus, PLC
XV-152-D8-10TVRC-10

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > HMI Touch Terminals
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton XV-152 Touch panel Catalog Number 150612 Model Code XV-152-D8-10TVRC-10 EAN
7640130097261 Product Length/Depth 345 mm Product Height 54 mm Product Width 260 mm Product Weight 2.95 kg
Certifications IEC/EN 61000-6-3

Security:

UL

UL File No.: E205091

UL508

CSA Class No.: none

UL 60950

CSA File No.: UL report applies to both US and Canada

CULus

UL Category Control No.: NRAQ

CUL508

EN 50178
EN 60950
ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x)
IEC/EN 61131-2
IEC/EN 61241-1 (ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x)
UL 508
DNV GL
IEC/EN 60079-0 (ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x)
IEC/EN 61000-6-2
IEC/EN 60950
IEC/EN 61131-2, CE
IEC/EN 61241-0 (ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x)
Certified by UL for use in Canada
IEC/EN 61000-6-4 Features & Functions
Enclosure material Metal, anodized Features UL508, cUL approvals
Slot for SD card
USB Host
Fanless CPU and system cooling, natural convection-based passive cooling
Overload proof
USB device
Portrait format
Ethernet interface Fitted with: 1 x RS232 (built-in interface)
Recipes
Numeric keyboard
Printer output
SW interfaces
Message indication
1 x USB device (built-in interface)
1 x RS485 (built-in interface)
1 x Ethernet 10/100 Mbps (built-in interfaces)
1 x USB host 2.0 (built-in interface)
1 x PROFIBUS/MPI (built-in interface)
Color display
Alpha numeric keyboard
Message system (incl. buffer an...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-152-D8-10TVRC-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.