

INDUSTRIAL COMPONENT DATA

XVS-430-57MPI-1-10 139967 EATON ELECTRIC Touch panel, 24 V DC, 5.7z, STNcolor, ethernet, RS232, profibus, (P..

Brand: EATON - MOELLER | Manufacturer Part Number: XVS-430-57MPI-1-10



Manufacturer	EATON - MOELLER
MPN / Reference	XVS-430-57MPI-1-10
Catalog number	139967
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-69B9EB8EC7
Generated	2026-08-06

Product Overview

Touch panel, 24 V DC, 5.7z, STNcolor, ethernet, RS232, profibus, (PLC)

Touch Terminal; 5.7" ; Resistive; STN Color; Ethernet; RS232; Profibus DP; PLC license not included

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > HMI Touch Terminals

Additional Product Information

Fuse-link, low voltage, 0.1 A, AC 250 V, 10 x 38 mm, supplemental, UL, CSA, time-delay Fuse, Fuse-link, low voltage, 0.1 A, AC 250 V, 10 x 38 mm, supplemental, UL, CSA, time-delay, cylindrical, colour-coded, green, general purpose, lighting circuits, meter circuits, UL 248-14, melamine tube [Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 0.1 A Rated voltage AC 250 V Size 10 x 38 mm Utilization category supplemental Description colour-coded

green usable for size/applications general purpose, lighting circuits, meter circuits Release characteristic [class] time-delay Standard/Approval UL

CSA Shape cylindrical Material melamine tube Standards/Regulations UL 248-14 , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) ()

[AFZ797013]) Size 10x38 mm Rated voltage 250 - 250 V Rated voltage Other Voltage type AC Utilization category Other Rated operating frequency 45 - 62 Hz Nominal current 0.1 A With striker No Release characteristic M (Midget) Breaking capacity 0.035 kA]

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XVS-430-57MPI-1-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.