

INDUSTRIAL COMPONENT DATA

XV-152-D4-57TVR-10 150526 Y7-150526 EATON ELECTRIC

Touch panel, 24 V DC, 5.7z, TFTcolor, ethernet, RS232, RS..

Brand: EATON - MOELLER | Manufacturer Part Number: XV-152-D4-57TVR-10



Manufacturer	EATON - MOELLER
MPN / Reference	XV-152-D4-57TVR-10
Catalog number	Y7-150526
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-1A0DEFF756
Generated	2026-08-05

Product Overview

Touch panel, 24 V DC, 5.7z, TFTcolor, ethernet, RS232, RS485, (PLC)

XV-152-D4-57TVR-10

User interface, XV-152, Product range: XV150 5.7z, Function: HMI-PLC (PLC retrofitted by user), Common features of the model series: Ethernet interface, USB device, USB Host, Slot for SD card, UL508, cUL approvals, Display - Type: Color display, TFT, Touch-technology: Resistive-Touch, Number of colors: 64 k Colors, Resolution: VGA, 640 x 480 Pixel, Portrait format: yes, Screen diagonal: 5.7 Inch, Metal enclosure and front plate, Operating system: Windows CE 5.0 (license incl.), PLC-license: Can be fitted by user with article no. 142581 LIC-PLC-MXP-COMPACT, License certificates for onboard interfaces: Not required , built-in interfaces: 1 x Ethernet 10/100 Mbps, 1 x RS232, 1 x RS485, 1 x USB host 2.0, 1 x USB device, Front type: Standard front with standard membrane (fully enclosed), Utilization: Flush mounting, Slots: for SD card: 1, Memory card automation: Optionally with SD card -> article no. 139807, Pluggable communication cards (optional): no, Touch sensor: Glass with film, Heat dissipation: 9.5 W, Degree of protection (IEC/EN 60529, EN50178, VBG 4): IP65 (at front), IP20 (at rear), Enclosure Type 4X (Indoor use only)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > HMI Touch Terminals
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton XV-152 Touch panel Catalog Number 150526 Model Code XV-152-D4-57TVR-10 EAN

7640130097100 Product Length/Depth 212 mm Product Height 52.5 mm Product Width 156 mm Product Weight 1.3 kg

Certifications ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x)

EN 60950
IEC/EN 61000-6-2
IEC/EN 61241-0 (ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x)
UL 508
Certified by UL for use in Canada
IEC/EN 60950
IEC/EN 61241-1 (ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x)
Security:
CSA Class No.: none
IEC/EN 61000-6-3
CSA File No.: UL report applies to both US and Canada
CUL508
CULus
DNV GL
IEC/EN 60079-0 (ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x)
UL File No.: E205091
EN 50178
IEC/EN 61131-2, CE
UL Category Control No.: NRAQ
IEC/EN 61000-6-4
UL
UL 60950
UL508
IEC/EN 61131-2
EAC Features & Functions
Enclosure material Metal, anodized Features Ethernet interface
UL508, cUL approvals
Fanless CPU and system cooling, natural convection-based passive cooling
Portrait format
Slot for SD card
USB device
USB Host
Overload proof Fitted with: 1 x USB host 2.0 (built-in interface)
Message system (incl. buffer and confirmation)
1 x USB device (built-in interface)
1 x Ethernet 10/100 Mbps (built-in interfaces)
Numeric keyboard
Recipes
1 x RS485 (built-in interface)
Color display
1 x RS232 (built-in interface)
Message indication
SW interfaces
Alpha numeric keyboard
Printer output Functions Addition...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-152-D4-57TVR-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.