

INDUSTRIAL COMPONENT DATA

XV-102-D4-57TVR-10 150620 Y7-150620 EATON ELECTRIC

Touch panel, 24 V DC, 5.7z, TFTcolor, ethernet, RS232, RS..

Brand: EATON - MOELLER | Manufacturer Part Number: XV-102-D4-57TVR-10



Manufacturer	EATON - MOELLER
MPN / Reference	XV-102-D4-57TVR-10
Catalog number	Y7-150620
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-C97E815E13
Generated	2026-08-06

Product Overview

Touch panel, 24 V DC, 5.7z, TFTcolor, ethernet, RS232, RS485, (PLC)
XV-102-D4-57TVR-10

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > HMI Touch Terminals

Additional Product Information

General specifications

Product Name Eaton XV-102 Touch panel Catalog Number 150620 Model Code XV-102-D4-57TVR-10 EAN 7640130097063 Product Length/Depth 170 mm Product Height 39 mm Product Width 130 mm Product Weight 0.54 kg

Certifications CUL508

UL 60950

IEC/EN 61000-6-2

Certified by UL for use in Canada

CSA File No.: UL report applies to both US and Canada

CSA Class No.: none

UL

UL Category Control No.: NRAQ

IEC/EN 61131-2, CE

EN 50178

EN 60950

IEC/EN 61000-6-4

DNV GL

CULus

UL508

IEC/EN 61131-2

UL File No.: E205091

EAC Features & Functions

Enclosure material Plastic Features USB device

Fanless CPU and system cooling, natural convection-based passive cooling

Slot for SD card

UL508, cUL approvals

Ethernet interface

USB Host

Portrait format Fitted with: 1 x Ethernet 10/100 Mbps (built-in interfaces)

Color display

1 x USB host 2.0 (built-in interface)

1 x RS485 (built-in interface)

Numeric keyboard

Message system (incl. buffer and confirmation)

SW interfaces

Message indication

Alpha numeric keyboard

Printer output

1 x RS232 (built-in interface)

1 x USB device (built-in interface)

Recipes Functions Additional software components, loadable

Process value representation (output) possible

Process default value (input) possible General

Battery runtime Back-up of real-time clock: CR 2032 (190 mA/h), zero maintenance (soldered) Degree of protection IP20

IP20, rear Degree of protection (front side) IP65

NEMA 4X Fuse type Built-in fuse (not accessible) Lifespan 40,000 h (Service life of....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-102-D4-57TVR-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.