

INDUSTRIAL COMPONENT DATA

XV-152-D6-84TVR-10 150603 Y7-150603 EATON ELECTRIC

Touch panel, 24 V DC, 8.4z, TFTcolor, ethernet, RS232, RS..

Brand: EATON - MOELLER | Manufacturer Part Number: XV-152-D6-84TVR-10



Manufacturer	EATON - MOELLER
MPN / Reference	XV-152-D6-84TVR-10
Catalog number	Y7-150603
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-8E375A0A46
Generated	2026-08-06

Product Overview

Touch panel, 24 V DC, 8.4z, TFTcolor, ethernet, RS232, RS485, CAN, (PLC)

XV-152-D6-84TVR-10

User interface, XV-152, Product range: XV150 8.4z, Function: HMI-PLC (PLC retrofitted by user), Common features of the model series: Ethernet interface, USB device, USB Host, Slot for SD card, UL508, cUL approvals, Display - Type: Color display, TFT, Touch-technology: Resistive-Touch, Number of colors: 64 k Colors, Resolution: VGA, 640 x 480 Pixel, Portrait format: yes, Screen diagonal: 8.4 Inch, Metal enclosure and front plate, Operating system: Windows CE 5.0 (license incl.), PLC-license: Can be fitted by user with article no. 142581 LIC-PLC-MXP-COMPACT, License certificates for onboard interfaces: Not required , built-in interfaces: 1 x Ethernet 10/100 Mbps, 1 x RS232, 1 x RS485, 1 x USB host 2.0, 1 x USB device, 1 x CANopen®/easyNet, Front type: Standard front with standard membrane (fully enclosed), Utilization: Flush mounting, Slots: for SD card: 1, Memory card automation: Optionally with SD card -> article no. 139807, Pluggable communication cards (optional): no, Touch sensor: Glass with film, Heat dissipation: 14.5 W, Degree of protection (IEC/EN 60529, EN50178, VBG 4): IP65 (at front), IP20 (at rear), Enclosure Type 4X (Indoor use only)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > HMI Touch Terminals
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton XV-152 Touch panel Catalog Number 150603 Model Code XV-152-D6-84TVR-10 EAN

7640130097155 Product Length/Depth 275 mm Product Height 52.5 mm Product Width 208 mm Product Weight 2.15 kg

Certifications UL 60950

EN 60950
IEC/EN 61000-6-3
UL508
CULus
IEC/EN 60079-0 (ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x)
UL 508
CSA Class No.: none
CSA File No.: UL report applies to both US and Canada
IEC/EN 61131-2, CE
DNV GL
UL File No.: E205091
Security:
Certified by UL for use in Canada
IEC/EN 60950
IEC/EN 61131-2
IEC/EN 61241-1 (ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x)
IEC/EN 61241-0 (ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x)
UL
ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x)
CUL508
UL Category Control No.: NRAQ
IEC/EN 61000-6-4
EN 50178
IEC/EN 61000-6-2
EAC Features & Functions
Enclosure material Metal, anodized Features Fanless CPU and system cooling, natural convection-based passive cooling
UL508, cUL approvals
Slot for SD card
USB Host
USB device
Portrait format
Overload proof
Ethernet interface Fitted with: 1 x RS485 (built-in interface)
Alpha numeric keyboard
SW interfaces
1 x CANopen®/easyNet (built-in interfaces)
Message system (incl. buffer and confirmation)
Color display
Numeric keyboard
1 x USB device (built-in interface)
Recipes
1 x Ethernet 10/100 Mbps (built-in interfaces)
1 x USB host 2.0 (built-in interface)
1 x RS232 (built-in interface)
Message....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-152-D6-84TVR-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.