

INDUSTRIAL COMPONENT DATA

XV-440-10TVB-1-10 139904 EATON ELECTRIC Touch panel, ir, 24 V DC, 10.4z, TFTcolor, ethernet, RS232, CAN, (PL..

Brand: EATON - MOELLER | Manufacturer Part Number: XV-440-10TVB-1-10



Manufacturer	EATON - MOELLER
MPN / Reference	XV-440-10TVB-1-10
Catalog number	139904
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-0DC55623EA
Generated	2026-08-06

Product Overview

Touch panel, ir, 24 V DC, 10.4z, TFTcolor, ethernet, RS232, CAN, (PLC)

Touch Terminal; 10.4" ; Infrared; TFT Color; Ethernet; RS232; DOG; PLC license not included

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > HMI Touch Terminals
--------------	---------------------------------------

Additional Product Information

Touch panel, ir, 24 V DC, 10.4z, TFTcolor, ethernet, RS232, CAN, (PLC) User interface, XV400, Product range: XV400 10.4", Function: HMI-PLC (PLC retrofitted by user), Common features of the model series: Ethernet interface, USB device, RS232, CAN/easyNet, UL508, cUL approvals, PLC function can be fitted by user, Communications scope can be fitted by user with licenses, Display - Type: Color display, TFT, Touch-technology: Infra-red touch, Number of colours: Adjustable: 65536 or 256 colours, Resolution: VGA, 640 x 480 Pixel, Portrait format: yes, Screen diagonal: 10.4 Inch, Metal enclosure and front plate, Operating system: Windows CE (license required), CompactFlash card required, PLC-licence: Can be fitted by user with article no. 140390 LIC-PLC-MXP-MEDIUM, License certificates for onboard interfaces: Can be expanded as required, see Accessories -> License product certificates, built-in interfaces: 1 x Ethernet 100base-TX/10base-T, 1 x RS232, 1 x CAN, 2 x USB host, 1 x USB device, Front type: Standard front with standard membrane, Laminated safety glass, non-reflective, Utilization: Flush mounting, Slots: for Compact-FlashTM-Cards: 2, for communication modules: 2, Memory card automation: required, see Accessories -> Memory cards, Pluggable communication cards (optional): yes, Heat dissipation: 32 W, Degree of protection (IEC/EN 60529, EN50178, VBG 4): IP65 (at front), IP20 (at rear) Delivery program

Product range XV400 10.4" Product range XV400 Function HMI-PLC (SPS functio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-440-10TVB-1-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.