

INDUSTRIAL COMPONENT DATA

XVS-460-84MPI-1-10 139971 EATON ELECTRIC Touch panel, ir, 24 V DC, 8.4 inch, TFT color, ethernet, RS232, pro..

Brand: EATON - MOELLER | Manufacturer Part Number: XVS-460-84MPI-1-10



Manufacturer	EATON - MOELLER
MPN / Reference	XVS-460-84MPI-1-10
Catalog number	139971
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-3A22CF5331
Generated	2026-08-06

Product Overview

Touch panel, ir, 24 V DC, 8.4 inch, TFT color, ethernet, RS232, profibus, (PLC)

Touch Terminal; 8.4" ; Infrared; TFT Color; Ethernet; RS232; Profibus DP; PLC license not included

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > HMI Touch Terminals**

Additional Product Information

Touch panel, ir, 24 V DC, 8.4z, TFTcolor, ethernet, RS232, profibus, (PLC) User interface, XVS400, Product range: XVS400 8.4", Function: HMI-PLC (PLC retrofitted by user), Common features of the model series: Ethernet interface, USB device, RS232, Profibus/MPI, UL508, cUL approvals, PLC function can be fitted by user, Communications scope can be fitted by user with licenses, Display - Type: Color display, TFT, Touch-technology: Infra-red touch, Number of colours: Adjustable: 65536 or 256 colours, Resolution: VGA, 640 x 480 Pixel, Portrait format: yes, Screen diagonal: 8.4 Inch, Metal enclosure and front plate, Operating system: Windows CE (license required), CompactFlash card required, PLC-licence: Can be fitted by user with article no. 140389 LIC-PLC-MXP-SMALL, License certificates for onboard interfaces: Can be expanded as required, see Accessories -> License product certificates, built-in interfaces: 1 x Ethernet 100base-TX/10base-T, 1 x RS232, 1 x PROFIBUS/MPI, 1 x USB host, 1 x USB device, Front type: Standard front with standard membrane, Laminated safety glass, non-reflective, Utilization: Flush mounting, Slots: for Compact-FlashTM-Cards: 1, Memory card automation: required, see Accessories -> Memory cards, Pluggable communication cards (optional): no, Heat dissipation: 22 W, Degree of protection (IEC/EN 60529, EN50178, VBG 4): IP65 (at front), IP20 (at rear) Delivery program

Product range XVS400 8.4" Product range XVS400 Function HMI-PLC (SPS function, retrofittable)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XVS-460-84MPI-1-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.