

INDUSTRIAL COMPONENT DATA

TR-G/8 272480 Y7-272480 EATON ELECTRIC Transformer 230V, 8 V, 1A, 2HP

Brand: EATON - MOELLER | Manufacturer Part Number: TR-G/8



Manufacturer	EATON - MOELLER
MPN / Reference	TR-G/8
Catalog number	Y7-272480
Category	Bell transformer
Minimum order	1 Pcs
Document ID	EO-CB8481221D
Generated	2026-08-02

Product Overview

Transformer 230V, 8 V, 1A, 2HP

TR-G/8

Eaton Distribution parts. Transformer 230V, 8 V, 1A, 2HP

Bell transformer with separate windings according to EN 61558, surface mounted mounting kit as an accessory (mounting plate), terminal shroud)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 272480 Model Code TR-G/8 EAN 4015082724801 Product Length/Depth 55 mm Product Height 90 mm Product Width 36 mm Product Weight 0.241 kg Compliances RoHS conform

Product specifications

Features Modular version

Short-circuit protected

Temperature protection Transformer type Standard bell ringing transformer Ambient operating temperature - max 40 °C

Ambient operating temperature - min -25 °C Heat dissipation capacity 0 W Heat dissipation per pole, current-dependent 0

W Output power - max 0 W Power loss - max 0 W Rated operational current for specified heat dissipation (In) 0 A

Secondary rated current 1 1 A Secondary rated current 2 0 A Secondary rated current 3 0 A Secondary voltage rating 1 8 V

Secondary voltage rating 2 0 V Secondary voltage rating 3 0 V Static heat dissipation, non-current-dependent 0 W Width in

number of modular spacings 2 Equipment heat dissipation, current-dependent 3.76 W Suitable for Surface mounting Output current - max 0 A Primary voltage 230 V

ETIM for 272480 Modular devices for distribution board/surface mounting (EC001547)

Feature Name

Feature Value

Primary voltage (EF003775)

230 V

Secondary voltage 1 (EF003776)

8 V

Secondary voltage 2 (EF003777)

0 V

Secondary voltage 3 (EF003778)

0 V

Secondary amperage 1 (EF003779)

1 A

Secondary amperage 2 (EF003780)

0 A

Secondary amperage 3 (EF003781)

0 A

Max. output power (EF001507)

0 W

Max. output current (EF001315)

0 A

Max. power loss (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TR-G/8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.