

INDUSTRIAL COMPONENT DATA

PKZM0-6,3-T 088915 Y7-88915 EATON ELECTRIC

Transformer-protective circuit-breaker, 3p, Ir 4-6.3A, screw conn..

Brand: EATON - MOELLER | Manufacturer Part Number: PKZM0-6,3-T



Manufacturer	EATON - MOELLER
MPN / Reference	PKZM0-6,3-T
Catalog number	Y7-88915
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-ECBC4652FE
Generated	2026-08-05

Product Overview

Transformer-protective circuit-breaker, 3p, Ir=4-6.3A, screw connection

Transformer Protective Switch 3 poles Ir=4-6.3 A Connection to

Eaton Moeller® series PKZM0 Transformer-protective circuit-breaker, 3p, Ir=4-6.3A, screw connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers PKZ
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKZM0 Transformer-protective circuit-breaker Catalog Number 088915 Model Code PKZM0-6,3-T EAN 4015080889151 Product Length/Depth 76 mm Product Height 93 mm Product Width 45 mm Product Weight 0.293 kg Certifications VDE 0660

IEC/EN 60947 Features & Functions

Actuator type Turn button Features Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102)

Complete device with protection unit Fitted with: Switched-off indicator Functions Transformer protection

For the protection of transformers with a high inrush current Number of poles Three-pole General

Lifespan, electrical 100,000 operations Lifespan, mechanical 100,000 Operations Mounting Method DIN rail (top hat rail)

mounting optional Mounting position Can be snapped on to IEC/EN 60715 top-hat rail with 7.5 or 15 mm height. Operating frequency 40 Operations/h Overvoltage category III Pollution degree 3 Product category Transformer protective circuit

breaker Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
Rated impulse withstand voltage (Uimp) 6000 V AC Shock resistance 25 g, Mechanical, according to IEC/EN 60068-2-27,
Half-sinusoidal shock 10 ms Suitable for Also motors with efficiency class IE3
DIN rail (top hat rail) mounting Temperature compensation $\leq 0.25\text{ \%}/\text{K}$, residual error for $T > 40^\circ$
-5 - 40 °C to IEC/EN 60947, VDE 0660
-25 - 55 °C, Operating range Climatic environmental conditions...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKZM0-6,3-T with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.