


INDUSTRIAL COMPONENT DATA

PKE-XTUA-1,2 121727 Y7-121727 EATON ELECTRIC Trip block, 0.3-1.2A, networkable, motor protection

Brand: EATON - MOELLER | Manufacturer Part Number: PKE-XTUA-1,2



Manufacturer	EATON - MOELLER
MPN / Reference	PKE-XTUA-1,2
Catalog number	Y7-121727
Category	Tripping bloc for power circuit-breaker
Minimum order	1 Pcs
Document ID	EO-7B7E139C16
Generated	2026-08-06

Product Overview

Trip block, 0.3-1.2A, networkable, motor protection

PKE-XTUA-1,2

Eaton Moeller® series PKE Trip block, 0.3 - 1.2 A, Motor protection, Connection to SmartWire-DT: yes, For use with: PKE12 basic device

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Electronic Circuit Breakers
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKE Trip block Catalog Number 121727 Model Code PKE-XTUA-1,2 EAN 4015081195374 Product Length/Depth 41.6 mm Product Height 64.2 mm Product Width 45 mm Product Weight 0.09 kg

Certifications CSA File No.: 165628

VDE 0660

CSA Class No.: 3211-05

IEC/EN 60947-4-1

CSA

UL Category Control No.: NLRV

IEC/EN 60947

CSA-C22.2 No. 14-10

UL

UL 508

CE

UL File No.: E36332 Catalog Notes This is a product for Environment A (Industrial). In environment B (household) this device may cause undesirable radio interference. In this case the user may be obliged to take appropriate measures.

Features & Functions

Features Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102) Functions Motor protection

Motor protection for heavy starting duty

Overload release Number of poles Three-pole General

Current flow times - min 700 (Class 10) AC-4 cycle operation, Main conducting paths

500 (Class 5) AC-4 cycle operation, Main conducting paths

Note: Going below the minimum current flow time can cause overheating of the load (motor).

900 (Class 15) AC-4 cycle operation, Main conducting paths

1000 (Class 20) AC-4 cycle operation, Main conducting paths

For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods. Cut-out periods - min ≤ 500 ms, main conducting paths, AC-4 cycle operation Degree of protection Device: IP20

Terminals: IP00 Operating frequency 60 Operations/h...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKE-XTUA-1,2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.