

INDUSTRIAL COMPONENT DATA

PKE-XTUCP-36 153164 Y7-153164 EATON ELECTRIC Trip block, 15-36A, system protection

Brand: EATON - MOELLER | Manufacturer Part Number: PKE-XTUCP-36



Manufacturer	EATON - MOELLER
MPN / Reference	PKE-XTUCP-36
Catalog number	Y7-153164
Category	Tripping bloc for power circuit-breaker
Minimum order	1 Pcs
Document ID	EO-B08854C792
Generated	2026-08-05

Product Overview

Trip block, 15-36A, system protection

PKE-XTUCP-36

Eaton Moeller® series PKE Trip block, 15 - 36 A, System protection, Connection to SmartWire-DT: no, For use with: PKE32 basic device

Electronic control option for system and cable protection according to IEC60947-2 for basic device PKE32, electronic wide-range overload protection (2.4: 1) adjustable short-circuit release. Mounting without tools with PKE basic device.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Electronic Circuit Breakers
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKE Trip block Catalog Number 153164 Model Code PKE-XTUCP-36 EAN 4015081498918 Product Length/Depth 41.6 mm Product Height 64.2 mm Product Width 45 mm Product Weight 0.09 kg Certifications VDE 0660

IEC/EN 60947 Catalog Notes This is a product for Environment A (Industrial). In environment B (household) this device may cause undesirable radio interference. In this case the user may be obliged to take appropriate measures. Features &

Functions

Functions Short-circuit protection

Line and cable protection

System protection

Overcurrent protection Number of poles Three-pole General

Current flow times - min 1000 (Class 20) AC-4 cycle operation, Main conducting paths

Note: Going below the minimum current flow time can cause overheating of the load (motor).

For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods.

500 (Class 5) AC-4 cycle operation, Main conducting paths

700 (Class 10) AC-4 cycle operation, Main conducting paths

900 (Class 15) AC-4 cycle operation, Main conducting paths Cut-out periods - min ≤ 500 ms, main conducting paths, AC-4 cycle operation Degree of protection Device: IP20

Terminals: IP00 Operating frequency 60 Operations/h Overload release current setting - min 15 A Overload release current setting - max 36 A Overvoltage category III Pollution degree 3 Product category Accessories Protection Finger and back-of-hand proof, Protection ag...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKE-XTUCP-36 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.