

INDUSTRIAL COMPONENT DATA

AGM2-01-PKZ0 072899 Y7-72899 EATON ELECTRIC Trip indicator switch, 2 N/C, screw connection

Brand: EATON - MOELLER | Manufacturer Part Number: AGM2-01-PKZ0



Manufacturer	EATON - MOELLER
MPN / Reference	AGM2-01-PKZ0
Catalog number	Y7-72899
Category	Auxiliary contact block
Minimum order	2 Pcs
Document ID	EO-8E68DA2A69
Generated	2026-08-02

Product Overview

Trip indicator switch, 2 N/C, screw connection

Trip Indicator Contact 1 NC For PKZ

Eaton Moeller® series PKZ Trip indicator, 2 x 1 NC, Screw terminals

Trip indicator switch 2 N/C, with screw terminal, for circuit-breaker PKZ(M)0 size

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers PKZ
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKZ Trip indicator Catalog Number 072899 Model Code AGM2-01-PKZ0 EAN 4015080728993 Product Length/Depth 68 mm Product Height 90 mm Product Width 23 mm Product Weight 0.035 kg

Certifications CE

IEC/EN 60947-4-1

CSA File No.: 165628

CSA-C22.2 No. 14

UL File No.: E36332

CSA Class No.: 3211-05

UL 508

CSA

UL Category Control No.: NLRV

UL Features & Functions

Electric connection type Screw connection Indication General trip indication (overload)

Short-circuits indicated locally by means of a red indicator that can be manually reset General

Lifespan, electrical 50,000 Operations Lifespan, mechanical 10,000 Operations Model Top mounting Mounting method Side mounting Overvoltage category III Pollution degree 3 Product category Accessories Rated impulse withstand voltage (Uimp)

6000 V AC Used with Motor protective circuit-breaker Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Terminal capacities

Terminal capacity (solid/flexible with ferrule) 0.75 - 2.5 mm² Terminal capacity (solid/stranded AWG) 18 - 14 Electrical rating

Rated operational current (Ie) 1 A at AC-15, 440 V 500 V Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V 3.5 A

Rated operational current (Ie) at AC-15, 380 V, 400 V, 415 V 2 A Rated operational current (Ie) at DC-13, 110 V 0.5 A

Rated operational current (Ie) at DC-13, 220 V, 230 V 0.25 A Rated operational current (Ie) at DC-13...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AGM2-01-PKZ0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.