

INDUSTRIAL COMPONENT DATA

AGM2-10-PKZ0 072898 Y7-72898 EATON ELECTRIC Trip indicator switch, 2N/O, screw connection

Brand: EATON - MOELLER | Manufacturer Part Number: AGM2-10-PKZ0



Manufacturer	EATON - MOELLER
MPN / Reference	AGM2-10-PKZ0
Catalog number	Y7-72898
Category	Auxiliary contact block
Minimum order	2 Pcs
Document ID	EO-5183FD5BFE
Generated	2026-08-03

Product Overview

Trip indicator switch, 2N/O, screw connection
Contact trigger indicator. 1 NO. For PKZ
Eaton Moeller® series PKZ Trip indicator, 2 x 1 N/O, Screw terminals

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers PKZ**

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKZ Trip indicator Catalog Number 072898 Model Code AGM2-10-PKZ0 EAN 4015080728986 Product Length/Depth 68 mm Product Height 90 mm Product Width 23 mm Product Weight 0.035 kg
Certifications CSA Class No.: 3211-05
UL File No.: E36332
CE
IEC/EN 60947-4-1
UL Category Control No.: NLRV
UL
CSA-C22.2 No. 14
CSA
CSA File No.: 165628
UL 508 Features & Functions

Electric connection type Screw connection Indication Short-circuits indicated locally by means of a red indicator that can be manually reset

General trip indication (overload) General

Lifespan, electrical 50,000 Operations Lifespan, mechanical 10,000 Operations Model Top mounting Mounting method Side mounting Overvoltage category III Pollution degree 3 Product category Accessories Rated impulse withstand voltage (Uimp) 6000 V AC Used with Motor protective circuit-breaker Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Terminal capacities

Terminal capacity (solid/flexible with ferrule) 0.75 - 2.5 mm² Terminal capacity (solid/stranded AWG) 18 - 14 Electrical rating

Rated operational current (Ie) 1 A at AC-15, 440 V 500 V Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V 3.5 A

Rated operational current (Ie) at AC-15, 380 V, 400 V, 415 V 2 A Rated operational current (Ie) at DC-13, 110 V 0.5 A

Rated operational current (Ie) at DC-13, 220 V, 230 V 0.25 A Rated operational current (Ie) at DC-13...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AGM2-10-PKZ0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.