

INDUSTRIAL COMPONENT DATA

TTM500 EATON ELECTRIC Fuse-link, low voltage, 500 A, AC 660 V, DC 450 V, BS88/C2, 74 x 210 mm, gL/gG, BS

Brand: EATON - MOELLER | Manufacturer Part Number: TTM500



Manufacturer	EATON - MOELLER
MPN / Reference	TTM500
Catalog number	10000
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-B85B611303
Generated	2026-08-06

Product Overview

500A 660V AC / 450V DC BS88 FUSE

Fuse-link, low voltage, 500 A, AC 660 V, DC 450 V, BS88/C2, 74 x 210 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 500 A, AC 660 V, DC 450 V, BS88/C2, 74 x 210 mm, gL/gG, BS, centre-bolted tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number TTM500 EAN 5996516026694

Product Length/Depth 210 mm Product Height 75 mm Product Width 75 mm Product Weight 1074 g Compliances CE

Marked

RoHS Compliant Certifications BS88

IEC 60269

KEMA

EAC Product specifications

Type Fuse Application general industrial applications Amperage Rating 500 A Fitted with: Centre bolted tags Fuse size BS88/C2 Current type AC/DC Mounting dimension M10 Center-to-center distance of connections 183.8 mm Breaking capacity 80 kA Rated switching capacity 80 kA Rated voltage AC 660 V Rated voltage DC 450 V Class Class gG/gL Fuse type TTM Utilization category gL/gG (cable protection/equipment protection) Color None Interrupt rating 80 kAIC Fuse

indicator None Insulated metal gripping lugs (IMGL) No Connection 133/184 mm fixing centre Construction BS88/C2
Construction size C2 Fuse shape Center bolted tags Voltage type AC/DC Voltage rating 660 V Fuse system (according to IEC 60269) Fuse system E
ETIM for TTM500 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Fuse system E
Fuse construction type according to IEC 60269 (EF015865)
C2
Type of current (EF000143)
AC/DC
Rated voltage AC (EF007682)
660 V
Rated voltage DC (EF012281)
450 V
Rated current (EF000227)
500 A
Utilization category according to IEC 60269 (EF002572)
gG (cable protection/equipment protection)
Breaking capacity (EF005617)
80 k...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TTM500 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.