

INDUSTRIAL COMPONENT DATA

NZM3-4-XKA2 271462 Y7-271462 EATON ELECTRIC Tunnel terminal, 4p, 1 page, max. 240mm², size 3

Brand: EATON - MOELLER | Manufacturer Part Number: NZM3-4-XKA2



Manufacturer	EATON - MOELLER
MPN / Reference	NZM3-4-XKA2
Catalog number	Y7-271462
Category	Wiring set for power circuit breaker
Minimum order	1 Pcs
Document ID	EO-F8EB134131
Generated	2026-08-05

Product Overview

Tunnel terminal, 4p, 1 page, max. 240mm², size 3

NZM3-4-XKA2

Eaton Moeller series NZM - Molded Case Circuit Breaker. Tunnel terminal, 4p, 1 page, max. 240mm², size 3

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: part no. contains parts for a terminal located at top or bottom for 3 or 4 pole switches. A standard with control circuit terminal for 1x0.75-2.5 mm² (18-14 AWG) or 2x0.75-1.5 mm² (18-16 AWG) copper conductors. Fitted outside the switch housing use ferrules with flexible and highly flexible conductors. Max. cross section shown can only be connected when flexible and without ferrules . Cover NZM3(-4)-XKSA must be fitted (included as standard). Can be used for: NZM3(-4), PN3(-4), N(N/O)3(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM connection type Catalog Number 271462 Model Code NZM3-4-XKA2 EAN

4015082714628 Product Length/Depth 190 mm Product Height 105 mm Product Width 105 mm Product Weight 1.514 kg

Compliances IEC

RoHS conform Certifications IEC 60947

EN 60947 Product specifications

Type Amperage Rating 630 A 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation.

Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation Meets the product standard's requirements. 10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated. 10.2.6 Mechanical impact Doe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM3-4-XKA2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.