

INDUSTRIAL COMPONENT DATA

Z-S/WM 248345 Y7-248345 EATON ELECTRIC Two way switchp11 CO, 16A, 230 V, 20kA

Brand: EATON - MOELLER | Manufacturer Part Number: Z-S/WM



Manufacturer	EATON - MOELLER
MPN / Reference	Z-S/WM
Catalog number	Y7-248345
Category	Main switch for distribution board
Minimum order	12 Pcs
Document ID	EO-6EA6A31C47
Generated	2026-08-04

Product Overview

Two way switchp11 CO, 16A, 230 V, 20kA

Z-S/WM

Eaton Distribution parts. Two way switchp11 CO, 16A, 230 V, 20kA, I-O-II

Changeover switch, function: 1W, I-O-II, rated operational current 16A, rated operating voltage 230/400V AC, short-circuit strength 10kA, standard front dimension 45 mm, mounting width 1 SU (17.5mm), top-hat rail mounting, terminal cross-section 1-10 mm², type conform to IEC 60669, VDE 0632

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 248345 Model Code Z-S/WM EAN 4015082483456 Product Length/Depth 80 mm Product Height 75 mm Product Width 17.5 mm Product Weight 0.063 kg Compliances RoHS conform Product specifications

Rated operational voltage (Ue) - max 240 V Voltage rating - min 0 V Width in number of modular spacings 1 Number of poles Single-pole Color calotte Other Switch type Two-way switch Rated short-time withstand current (Icw) 10 kA Lamp socket Other Built-in depth 80 mm Amperage rating 20 A Voltage type AC Lamp type Other Degree of protection IP40 Lamp power 0 W Number of contacts (change-over contacts) 1 Number of contacts (normally closed contacts) 0 Number of contacts (normally open contacts) 0 Inscription Other Rated operational current for specified heat dissipation (In) 20 A Rated Switching Capacity 0.02 kA

ETIM for 248345 Modular devices for distribution board/surface mounting (EC001545)

Feature Name

Feature Value

Switching function (EF000189)

Two-way switch

Number of contacts as normally open contact (EF008256)

0

Number of contacts as normally closed contact (EF008255)

0

Number of contacts as change-over contact (EF008257)

1

Number of poles (EF001391)

1

Rated current (EF000227)

20 A

Rated voltage (EF000228)

240 V

Min. rated voltage (EF005025)

0 V

Rated switching capacity (EF002563)

0.02 kA

Short-circuit breaking capacity (I_{cn}) (EF002562)

10 kA

Voltage type (EF000187)

AC

With signal lamp (EF000198)

No

Colour calotte...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-S/MM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.