

INDUSTRIAL COMPONENT DATA

U-PKZ0(24V50HZ)-PI 199332 Y7-199332 EATON ELECTRIC

U-PKZ0(24V50HZ)-PI

Brand: EATON - MOELLER | Manufacturer Part Number: U-PKZ0(24V50HZ)-PI



Manufacturer	EATON - MOELLER
MPN / Reference	U-PKZ0(24V50HZ)-PI
Catalog number	Y7-199332
Category	Under voltage coil
Minimum order	1 Pcs
Document ID	EO-982EA2E32F
Generated	2026-08-06

Product Overview

U-PKZ0(24V50HZ)-PI

Eaton Moeller® series U-PKZ0 Undervoltage release PKZ0(4), PKE, AC, 24 V 50 Hz, Push in terminals
Undervoltage release, non-delayed, for circuit-breaker PKZ(M)0 size, Push in terminals

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton Moeller® series U-PKZ0 Accessory Undervoltage Release Catalog Number 199332 Model Code U-PKZ0(24V50HZ)-PI EAN 4015081974160 Product Length/Depth 68 mm Product Height 91 mm Product Width 24 mm Product Weight 0.134 kg Compliances RoHS conform

CE Marked Catalog Notes Cannot be combined with A-PKZ0 shunt release Features & Functions

Electric connection type Spring clamp connection General

Suitable as EMERGENCY STOP or EMERGENCY switching-off device in accordance with IEC/EN 60204 when combined with circuit breaker Suitable for Motor safety switch Used with Motor protective circuit-breaker Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Terminal capacities

Terminal capacity (solid/stranded AWG) 20 - 14 Electrical rating

Rated operational voltage (Ue) at AC - min 42 V Rated operational voltage (Ue) at AC - max 480 V Rated operational voltage (Ue) at DC - min 24 V Rated operational voltage (Ue) at DC - max 250 V Magnet system

Drop-out voltage 0,7- 0,35 x U_c Pick-up voltage 0.85 - 1.1 V x U_c Rated control supply voltage (Us) at AC, 50 Hz - min 24 V
Rated control supply voltage (Us) at AC, 50 Hz - max 24 V Rated control supply voltage (Us) at AC, 60 Hz - min 0 V Rated
control supply voltage (Us) at AC, 60 Hz - max 0 V Rated control supply voltage (Us) at DC - min 0 V Rated control supply
voltage (Us) at DC - max 0 V Contacts
Number of contacts (change-over....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / U-PKZ0(24V50HZ)-PI with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.