

INDUSTRIAL COMPONENT DATA

U-PKZ0(24V60HZ) 219219 Y7-219219 EATON ELECTRIC

Undervoltage release, 24V60Hz

Brand: EATON - MOELLER | Manufacturer Part Number: U-PKZ0(24V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	U-PKZ0(24V60HZ)
Catalog number	Y7-219219
Category	Under voltage coil
Minimum order	1 Pcs
Document ID	EO-E3ED04AB9E
Generated	2026-08-05

Product Overview

Undervoltage release, 24V60Hz

U-PKZ0(24V60HZ)

Eaton Moeller® series U-PKZ0 Undervoltage release PKZ0(4), PKE, AC, 24 V 60 Hz, Screw terminals

Undervoltage release, non-delayed, for circuit-breaker PKZ(M)0 size

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton Moeller® series U-PKZ0 Accessory Undervoltage Release Catalog Number 219219 Model Code

U-PKZ0(24V60HZ) EAN 4015082192198 Product Length/Depth 68 mm Product Height 90 mm Product Width 24 mm

Product Weight 0.137 kg Certifications UL 508

CSA Class No.: 3211-05

CSA-C22.2 No. 14

CSA

CSA File No.: 165628

CE

UL Category Control No.: NLRV

UL File No.: E36332

IEC/EN 60947-4-1

UL General

Mounting position Can be fitted to left side of the motor protection switch Product category Accessories Suitable as EMERGENCY STOP or EMERGENCY switching-off device in accordance with IEC/EN 60204 when combined with circuit breaker Suitable for Motor safety switch Used with Motor protective circuit-breaker Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Terminal capacities

Terminal capacity (solid/flexible with ferrule) 1 x (0.75 - 2.5) mm²

2 x (0.75 - 2.5) mm² Terminal capacity (solid/stranded AWG) 1 x (18 - 14)

2 x (18 - 14) Electrical rating

Rated operational voltage (Ue) at AC - min 42 V Rated operational voltage (Ue) at AC - max 480 V Rated operational

voltage (Ue) at DC - min 24 V Rated operational voltage (Ue) at DC - max 250 V Magnet system

Drop-out voltage 0,7- 0,35 x U_c Pick-up voltage 0.85 - 1.1 V x U_c Rated control supply voltage (Us) at AC, 50 Hz - min 0 V

Rated control supply voltage (Us) at AC, 50 Hz - max 0 V Rated control supply voltage (Us) at AC, 60 Hz -....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / U-PKZ0(24V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.