

INDUSTRIAL COMPONENT DATA

NZM2/3-XUHIV2048AC 259643 Y7-259643 EATON ELECTRIC

Under Undervoltage release, 48VAC, +2N/O early

Brand: EATON - MOELLER | Manufacturer Part Number: NZM2/3-XUHIV2048AC



Manufacturer	EATON - MOELLER
MPN / Reference	NZM2/3-XUHIV2048AC
Catalog number	Y7-259643
Category	Under voltage coil
Minimum order	1 Pcs
Document ID	EO-06A0F5EF08
Generated	2026-08-03

Product Overview

Under Undervoltage release, 48VAC, +2N/O early

NZM2/3-XUHIV2048AC

Eaton Moeller series NZM - Molded Case Circuit Breaker. Under Undervoltage release, 48VAC, +2N/O early

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: for interlocking and load-shedding circuits, as well as for early-make of the undervoltage release in main-switch applications. For use with Emergency-Stop devices in conjunction with emergency-stop button. when the shunt release is energized, accidental contact with the main contacts of the switch during attempts to switch on is safely prevented . Early make of auxiliary contacts on switching on and off (manual operation): approx. 20ms. Cannot be used in conjunction with NZM...-XR.. remote operator. Undervoltage releases cannot be installed simultaneously with NZM...-XHIV.. early-make auxiliary contact or NZM...-XA.. shunt release. Can be used for: NZM2(-4), N(N/O)2(-4), NZM3(-4), N(N/O)3(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM release Catalog Number 259643 Model Code NZM2/3-XUHIV2048AC EAN 4015082596439 Product Length/Depth 42 mm Product Height 90 mm Product Width 30 mm Product Weight 0.074 kg

Compliances IEC

UL/CSA

RoHS conform Certifications CSA (Class No. 1437-01)

CSA (File No. 22086)

UL (Category Control Number DIHS)

CE marking

IEC60947

UL listed

CSA certified

UL (File No. E140305)

UL489

CSA-C22.2 No. 5-09 Product specifications

Type Accessory Undervoltage release Undervoltage release with early-make auxiliary contact Special features Undervoltage release with 2 early-make auxiliary contacts, e.g., for early-make connection of undervoltage release in main switch applications, as well as for interlock and load shedding circuits. For use with emergency-stop devices in connection with an emergency-stop button. If the shunt trip is live, contact with the circuit breaker's primary contacts is prevented when switched on. Early make of auxiliary contacts on switching on and off (manual operation): approx. 20 ms Cannot be used in conjunction with NZM...-XR... remote operator. Undervoltage releases cannot be installed simultaneously with NZM...-XHIV... early-make auxiliary contact or NZM...-XA... shunt release. 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM2/3-XUHIV2048AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.