INDUSTRIAL COMPONENT DATA

NZM1-XU110-130DC 259458 Y7-259458 EATON ELECTRIC Undervoltage release, 110-130VDC

Brand: EATON - MOELLER | Manufacturer Part Number: NZM1-XU110-130DC

Manufacturer	EATON - MOELLER
MPN / Reference	NZM1-XU110-130DC
Catalog number	Y7-259458
Category	Under voltage coil
Minimum order	1 Pcs
Document ID	EO-20C53F100E
Generated	2026-08-04

Product Overview

Undervoltage release, 110-130VDC
NZM1-XU110-130DC
Eaton Moeller series NZM - Molded Case Circuit Breaker. Undervoltage release, 110-130VDC, 1
Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: non-delayed disconnection of NZM circuit-breaker or N switch-disconnector when the control voltage sinks below 35-70% US. For use with Emergency-Stop devices in conjunction with emergency-stop button. when the undervoltage release is de-energized, accidental contact with the main contacts of the switch during attempts to switch on is safely prevented . Undervoltage releases cannot be installed simultaneously with NZM..-XHIV.. early-make auxiliary contact or NZM..-XA.. shunt release. Can be used for: NZM1(-4), N(N/O)1(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

General specifications
Product Name Eaton Moeller series NZM release Catalog Number 259458 Model Code NZM1-XU110-130DC EAN 4015082594589 Product Length/Depth 37 mm Product Height 66 mm Product Width 32 mm Product Weight 0.044 kg
Compliances UL/CSA
IEC
RoHS conform Certifications CSA (Class No. 1437-01)

UL (Category Control Number DIHS)
UL489
UL (File No. E140305)
CE marking
IEC60947
CSA certified
CSA (File No. 22086)
CSA-C22.2 No. 5-09
UL listed Product specifications
Type AccessoryUndervoltage release Special features Non-delayed disconnection of NZM circuit-breaker or N switch-disconnector when the control voltage sinks below 35 - 70% US.For use with emergency-stop devices in connection with an emergency-stop button.When the under-voltage trip is switched off, accidental contact with the circuit breaker’s primary contacts is prevented when switched on.Undervoltage releases cannot be installed simultaneously with NZM...-XHIV... early-make auxiliary contact or NZM...-XA... shunt release. 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in th...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM1-XU110-130DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.