

INDUSTRIAL COMPONENT DATA

FAZ-XUA(115VAC) 212049 Y7-212049 EATON ELECTRIC

Undervoltage release, 115 V, non-delayed, 1HP

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-XUA(115VAC)



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-XUA(115VAC)
Catalog number	Y7-212049
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-87A893E9B3
Generated	2026-08-05

Product Overview

Undervoltage release, 115 V, non-delayed, 1HP

FAZ-XUA(115VAC)

Eaton Distribution parts. Undervoltage release, 115 V, non-delayed, 1HP, 2x(1-2.5) mm²

Undervoltage release screwable, rated operating voltage 115V AC, non-delayed function, frequency 50-60hz, closing threshold 80% of Un, tripping threshold below 50% of Un, standard front dimension 45 mm, mounting width 1 SU (17.5mm), top-hat rail mounting, terminal cross-section 2x(1-2.5) mm² solid and flexible

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 212049 Model Code FAZ-XUA(115VAC) EAN 4015082120498

Product Length/Depth 80 mm Product Height 75.5 mm Product Width 17.5 mm Product Weight 0.105 kg Compliances

RoHS conform Certifications EN45545-2

IEC 61373 Catalog Notes 15VAC Product specifications

Type Accessory/spare part type Undervoltage release Degree of protection IP40 Frame Standard front dimension: 45 mm

Frequency rating 50 Hz / 60 Hz Used with Accessory

Accessory for miniature circuit breaker Mounting method Top-hat rail IEC/EN 60715 Additional equipment required Under voltage coil Terminal protection Protection against electric shock to IEC 536 Terminal type Twin-purpose terminals Tripping threshold 0.5 x Un Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Assembly width

1 TE Enclosure width 80 mm Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1 Number of poles at main contact unit - max 1 Number of switches (fault signal) 0 Voltage type AC Functions Under voltage coil Closing threshold $0.8 \times U_n$ Device fitting Miniature circuit breaker (MCB) Mounting width 17.5 mm (1 space unit) Rated operational voltage (U_e) - max 115 V Rated switch current 0 A Suitable for current of main contact unit - max 0 A Terminal capacity (cable) $1 \text{ mm}^2 - 2.5 \text{ mm}^2$ (2x) Terminal capacity (solid wire) $1 \text{ mm}^2 - 2.5 \text{ mm}^2$ (2x)
ETIM for 212049 Modular...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-XUA(115VAC) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.