

INDUSTRIAL COMPONENT DATA

NZM2/3-XU208-240AC 259499 Y7-259499 EATON ELECTRIC

Undervoltage release, 208-240VAC

Brand: EATON - MOELLER | Manufacturer Part Number: NZM2/3-XU208-240AC



Manufacturer	EATON - MOELLER
MPN / Reference	NZM2/3-XU208-240AC
Catalog number	Y7-259499
Category	Under voltage coil
Minimum order	1 Pcs
Document ID	EO-E82EBBFA4D
Generated	2026-08-03

Product Overview

Undervoltage release, 208-240VAC

NZM2/3-XU208-240AC

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: non-delayed disconnection of NZM circuit-breaker or N switch-disconnector when the control voltage sinks below 35-70% US. For use with Emergency-Stop devices in conjunction with emergency-stop button. when the undervoltage release is de-energized, accidental contact with the main contacts of the switch during attempts to switch on is safely prevented . Undervoltage releases cannot be installed simultaneously with NZM..-XHIV.. early-make auxiliary contact or NZM..-XA.. shunt release. Can be used for: NZM2(-4), N(N/O)2(-4), NZM3(-4), N(N/O)3(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Undervoltage release, 208-240VACOptional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: non-delayed disconnection of NZM circuit-breaker or N switch-disconnector when the control voltage sinks below 35-70% US. For use with Emergency-Stop devices in conjunction with emergency-stop button. when the undervoltage release is de-energized, accidental contact with the main contacts of the switch during attempts to switch on is safely prevented . Undervoltage releases cannot be installed simultaneously with NZM..-XHIV.. early-make auxiliary contact or NZM..-XA.. shunt release. Can be used for: NZM2(-4), N(N/O)2(-4), NZM3(-4), N(N/O)3(-4)

General specifications
Product name Eaton Moeller series NZM releasePart
no. NZM2/3-XU208-240ACEAN4015082594992
Product Length/Depth 42 millimetre
Product height 90 millimetre
Product width 30 millimetre
Product weight 0.097 kilogram
Compliances IEC
UL/CSA
RoHS conform
Certifications CSA certified
IEC60947
CSA (File No. 22086)
CSA (Class No. 1437-01)
UL (File No. E140305)
UL listed
UL (Category Control Number DIHS)
UL489
CE marking
CSA-C22.2 No. 5-09
Product Tradename NZM
Product Type Accessories
Product Sub Type Release
Delivery program Type Accessory
Undervoltage release
Special features Non-delayed disconnection of NZM circuit-breaker or N switch-disconnector when the control voltage sinks below 35 - 70% US.
For...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM2/3-XU208-240AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.