

INDUSTRIAL COMPONENT DATA

Z-USD/230 248291 Y7-248291 EATON ELECTRIC Undervoltage release, 230 V, delayed 0, 4N/O, 1HP

Brand: EATON - MOELLER | Manufacturer Part Number: Z-USD/230



Manufacturer	EATON - MOELLER
MPN / Reference	Z-USD/230
Catalog number	Y7-248291
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-381EB056AD
Generated	2026-08-04

Product Overview

Undervoltage release, 230 V, delayed 0, 4N/O, 1HP

Z-USD/230

Eaton Distribution parts. Undervoltage release, 230 V, delayed 0, 4N/O, 1HP

Undervoltage release screwable, rated operating voltage 230V AC, delayed function 0.4s, frequency 50-60hz, closing threshold 80% of Un, tripping threshold below 30% of Un, standard front dimension 45 mm, mounting width 1 MU (17.5mm), DIN-rail mounting, terminal cross-section 1-2x2.5 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 248291 Model Code Z-USD/230 EAN 4015082482916 Product Length/Depth 80 mm Product Height 65.5 mm Product Width 17.5 mm Product Weight 0.106 kg Compliances RoHS conform Certifications EN45545-2

IEC 61373 Product specifications

Used with Undervoltage releases

Accessory

Accessory for miniature circuit breaker Type Application Switchgear for industrial and advanced commercial applications

Accessory/spare part type Undervoltage release Mounting method For fitting on left to: FAZ Additional equipment required

Under voltage coil Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Assembly width 1

TE Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1 Number of poles at main contact unit - max 1 Number of switches (fault signal) 0 Voltage type AC Functions Under voltage coil Device fitting Universal Rated operational voltage (Ue) - max 230 V Rated switch current 0 A Suitable for current of main contact unit - max 0 A Tripping time Delayed 0.4 s
ETIM for 248291 Modular devices for distribution board/surface mounting (EC001286)
Feature Name
Feature Value
Device fitting (EF007826)
Universal
Function (EF000030)
Under voltage coil
Width in number of modular spacings (EF002950)
1
Number of contacts as normally open contact (EF008256)
1
Number of contacts as normally closed contact (EF008255)
1
Numbe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-USD/230 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.