

## INDUSTRIAL COMPONENT DATA

# NZM4-XU24DC 266204 Y7-266204 EATON ELECTRIC

## Undervoltage release, 24 V DC

Brand: EATON - MOELLER | Manufacturer Part Number: NZM4-XU24DC



|                 |                    |
|-----------------|--------------------|
| Manufacturer    | EATON - MOELLER    |
| MPN / Reference | NZM4-XU24DC        |
| Catalog number  | Y7-266204          |
| Category        | Under voltage coil |
| Minimum order   | 1 Pcs              |
| Document ID     | EO-54EABF4A9C      |
| Generated       | 2026-08-01         |

### Product Overview

Undervoltage release, 24 V DC

NZM4-XU24DC

Eaton Moeller series NZM - Molded Case Circuit Breaker. Undervoltage release, 24 V DC, 4

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: non-delayed disconnection of NZM circuit-breaker or N switch-disconnector when the control voltage sinks below 35-70% US. For use with Emergency-Stop devices in conjunction with emergency-stop button. when the undervoltage release is de-energized, accidental contact with the main contacts of the switch during attempts to switch on is safely prevented . Undervoltage releases cannot be installed simultaneously with NZM..-XHIV.. early-make auxiliary contact or NZM..-XA.. shunt release. Can be used for: NZM4(-4), N(N/O)4(-4)

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Circuit Breakers NZM

### Additional Product Information

General specifications

Product Name Eaton Moeller series NZM release Catalog Number 266204 Model Code NZM4-XU24DC EAN

4015082662042 Product Length/Depth 107 mm Product Height 51 mm Product Width 64 mm Product Weight 0.265 kg

Compliances UL/CSA

IEC

RoHS conform Certifications IEC60947

CSA (Class No. 1437-01)

UL (File No. E140305)

UL (Category Control Number DIHS)

CE marking

UL listed

UL489

CSA certified

CSA-C22.2 No. 5-09

CSA (File No. 22086) Product specifications

Type Special features Non-delayed disconnection of NZM circuit-breaker or N switch-disconnector when the control voltage sinks below 35 - 70% US.

For use with emergency-stop devices in connection with an emergency-stop button.

When the under-voltage trip is switched off, accidental contact with the circuit breaker's primary contacts is prevented when switched on.

Undervoltage releases cannot be installed simultaneously with NZM...-XHIV... early-make auxiliary contact or NZM...-XA... shunt release.

10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is o...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM4-XU24DC with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.