

INDUSTRIAL COMPONENT DATA

IZMX-UVR24DC 123744 EATON ELECTRIC Undervoltage release 24 VDC

Brand: EATON - MOELLER | Manufacturer Part Number: IZMX-UVR24DC



Manufacturer	EATON - MOELLER
MPN / Reference	IZMX-UVR24DC
Catalog number	123744
Category	Under voltage coil
Minimum order	1 Pcs
Document ID	EO-5FF4E44C8E
Generated	2026-07-29

Product Overview

Undervoltage release 24 VDC

IZMX-UVR24DC

Suitable for remote switching off, can be combined only with an undervoltage release

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers IZM

Additional Product Information

Undervoltage release 24 VDC Suitable for remote switching off, can be combined only with an undervoltage release [Delivery program

Product range Accessories Accessories Remote switching Accessories Undervoltage release Cannot be combined with a second shunt release.

Retrofitting kit

Slot on the right on the adapter plate. Maximum operating frequency [Actuations/minute] 3 Limited to 3/min due to the high pick-up current for 35 ms.

Please note - the circuit-breaker's switching frequency = 60/h Rated control voltage [Us] 24 V DC V Operating range [x US] 0,85 - 1,1 Factor max. holding current [In] 0.18 A max. pick-up current (35ms) [In] 19 A max. continuous power [AC/DC] 5 VA/W max. pull-in power (35ms) [AC/DC] 500 VA/W Circuit-breaker total switching time [@ US=100%] 37 ms For use with IZMX16..., IZMX40...

INX16..., INX40... Instructions An additional control circuit terminal block is required for retrofitting.

For fixed mounting circuit-breakers?#156593 and withdrawable unit circuit-breakers ?#156590 Notes Can be continuously

ON (100% DF)

, Design verification as per IEC/EN 61439

Operating ambient temperature min. -25 °C Operating ambient temperature max. +70 °C , Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Under voltage coil (EC001022) Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Undervoltage trip () [AKF015013]) Rated control supply voltage Us at AC 50...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IZMX-UVR24DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.