

INDUSTRIAL COMPONENT DATA

IZM-UVR24DC 122946 Y7-122946 EATON ELECTRIC

Undervoltage release, 24VDC

Brand: EATON - MOELLER | Manufacturer Part Number: IZM-UVR24DC



Manufacturer	EATON - MOELLER
MPN / Reference	IZM-UVR24DC
Catalog number	Y7-122946
Category	Under voltage coil
Minimum order	1 Pcs
Document ID	EO-44DDCC0095
Generated	2026-08-04

Product Overview

Undervoltage release, 24VDC

IZM-UVR24DC

Minimum voltage releases, 24VDC

Undervoltage release, For use with: IZM20, 32, 40, 63..., IN20, 32,40, 63..., If ordered separately a secondary terminal unit IZM-SEC-... is necessary for connection. Order separately if required. Terminal assignment page 71

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers IZM**

Additional Product Information

Undervoltage release, 24VDC Eaton Catalog No. 2A10705G03 Undervoltage release, For use with: IZM20, 32, 40, 63..., IN20, 32,40, 63..., If ordered separately a secondary terminal unit IZM-SEC-... is necessary for connection. Order separately if required. Terminal assignment page 71 [Delivery program

Accessories Voltage release Accessories Undervoltage release For use with IZM20, 32, 40, 63...

IN20, 32,40, 63... Instructions If ordered separately a secondary terminal unit IZM-SEC-... is necessary for connection.

Order separately if required. Terminal assignment page 71 , Technical data

Rated control voltage [Us] DC [Us] 24 V Power consumption DC 18 (pick-up 250) W Circuit-breaker response time at Us 70 ms Operating range Drop-out voltageAC operated, 50/60 Hz, pick-up [Drop-out] According to the IEC standard x Uc Pick-up voltage [Pick-up] According to the IEC standard x Uc , Design verification as per IEC/EN 61439

Operating ambient temperature min. -25 °C Operating ambient temperature max. +70 °C]

ETIM for 122946 Low-voltage industrial controls and switchgear (EC001022)

Feature Name

Feature Value

Rated control supply voltage AC 50 Hz (EF003978)

None V

Rated control supply voltage AC 60 Hz (EF003979)

None V

Rated control supply voltage DC (EF003980)

None V

Voltage type for actuating (EF008242)

Type of electric connection (EF003961)

Number of contacts as normally open contact (EF008256)

Number of contacts as normally closed contact (EF008255)

Number of contacts as change-over contact (EF00...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IZM-UVR24DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.