

INDUSTRIAL COMPONENT DATA

NZM1-XUVHIV20L 271609 Y7-271609 EATON ELECTRIC

Undervoltage release, 2early N/O, for delay unit, +cable

Brand: EATON - MOELLER | Manufacturer Part Number: NZM1-XUVHIV20L



Manufacturer	EATON - MOELLER
MPN / Reference	NZM1-XUVHIV20L
Catalog number	Y7-271609
Category	Under voltage coil
Minimum order	1 Pcs
Document ID	EO-D912C73970
Generated	2026-08-05

Product Overview

Undervoltage release, 2early N/O, for delay unit, +cable

NZM1-XUVHIV20L

Eaton Moeller series NZM - Molded Case Circuit Breaker. Undervoltage release, 2early N/O, for delay unit, +cable

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: non-delayed disconnection of NZM circuit-breaker or N switch-disconnector when the control voltage sinks below 35-70% US. For use with Emergency-Stop devices in conjunction with emergency-stop button. when the undervoltage release is de-energized, accidental contact with the main contacts of the switch during attempts to switch on is safely prevented . Undervoltage releases cannot be installed simultaneously with NZM..-XHIV.. early-make auxiliary contact or NZM..-XA.. shunt release. Can be used for: NZM1(-4), N(N/O)1(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers NZM**

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM release Catalog Number 271609 Model Code NZM1-XUVHIV20L EAN 4015082716097 Product Length/Depth 37 mm Product Height 66 mm Product Width 32 mm Product Weight 0.17 kg

Compliances IEC

RoHS conform Certifications UL489

CSA (Class No. 1437-01)

UL (File No. E140305)

CE marking

IEC60947

UL listed

CSA-C22.2 No. 5-09

UL (Category Control Number DIHS)

CSA (File No. 22086)

CSA certified Product specifications

Type Accessory Undervoltage release Undervoltage release for use with delay unit UVU Special features Combination of separate delay unit and special releases. For use with emergency-stop devices in connection with an emergency-stop button. not UL/CSA approved Special releases for combining with separate delay time. UVU-NZM delay unit is additionally required. Cannot be installed simultaneously with separate NZM...-XHIV early-make auxiliary contact or NZM...-XA... shunt release. Cannot be used in conjunction with NZM...-XR... remote operator. Early make of auxiliary contact on switching on and off (manual operation): approx. 20 ms. 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM1-XUVHIV20L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.