

INDUSTRIAL COMPONENT DATA

NZM4-XUVHIV 266596 Y7-266596 EATON ELECTRIC

Undervoltage release, 2early N/O, for delay unit

Brand: EATON - MOELLER | Manufacturer Part Number: NZM4-XUVHIV



Manufacturer	EATON - MOELLER
MPN / Reference	NZM4-XUVHIV
Catalog number	Y7-266596
Category	Under voltage coil
Minimum order	1 Pcs
Document ID	EO-173665FEBC
Generated	2026-08-04

Product Overview

Undervoltage release, 2early N/O, for delay unit

NZM4-XUVHIV

Eaton Moeller series NZM - Molded Case Circuit Breaker. Undervoltage release for switch frame size NZM4, with 2 early-make auxiliary contacts N/O, for combination with separate delay unit

Undervoltage release for switch frame size NZM4, with 2 early-make auxiliary contacts N/O, for combination with separate delay unit

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM release Catalog Number 266596 Model Code NZM4-XUVHIV EAN

4015082665968 Product Length/Depth 107 mm Product Height 51 mm Product Width 64 mm Product Weight 0.24 kg

Compliances IEC

RoHS conform Certifications CE marking

CSA certified

CSA (Class No. 1437-01)

UL (Category Control Number DIHS)

UL (File No. E140305)

UL listed

CSA-C22.2 No. 5-09

CSA (File No. 22086)

UL489

IEC60947 Product specifications

Used with N(S)4(-4)

NZM4(-4) Type Accessory Undervoltage release Undervoltage release for use with delay unit UVU Special features Combination of separate delay unit and special releases. For use with emergency-stop devices in connection with an emergency-stop button. not UL/CSA approved Special releases for combining with separate delay time. UVU-NZM delay unit is additionally required. Cannot be installed simultaneously with separate NZM...-XHIV early-make auxiliary contact or NZM...-XA... shunt release. Cannot be used in conjunction with NZM...-XR... remote operator. Early make of auxiliary contact on switching on (manual operation): approx. 90 ms. 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM4-XUVHIV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.