

## INDUSTRIAL COMPONENT DATA

# NZM2/3-XU380-440AC 259501 Y7-259501 EATON ELECTRIC

## Undervoltage release, 380-440VAC

Brand: EATON - MOELLER | Manufacturer Part Number: NZM2/3-XU380-440AC



|                 |                    |
|-----------------|--------------------|
| Manufacturer    | EATON - MOELLER    |
| MPN / Reference | NZM2/3-XU380-440AC |
| Catalog number  | Y7-259501          |
| Category        | Under voltage coil |
| Minimum order   | 1 Pcs              |
| Document ID     | EO-AE043C6478      |
| Generated       | 2026-08-05         |

### Product Overview

Undervoltage release, 380-440VAC

NZM2/3-XU380-440AC

Eaton Moeller series NZM - Molded Case Circuit Breaker. Undervoltage release, 380-440VAC, 2/3

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: non-delayed disconnection of NZM circuit-breaker or N switch-disconnector when the control voltage sinks below 35-70% US. For use with Emergency-Stop devices in conjunction with emergency-stop button. when the undervoltage release is de-energized, accidental contact with the main contacts of the switch during attempts to switch on is safely prevented . Undervoltage releases cannot be installed simultaneously with NZM..-XHIV.. early-make auxiliary contact or NZM..-XA.. shunt release. Can be used for: NZM2(-4), N(N/O)2(-4), NZM3(-4), N(N/O)3(-4)

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Circuit Breakers NZM

### Additional Product Information

General specifications

Product Name Eaton Moeller series NZM release Catalog Number 259501 Model Code NZM2/3-XU380-440AC EAN 4015082595012 Product Length/Depth 42 mm Product Height 90 mm Product Width 30 mm Product Weight 0.094 kg

Compliances UL/CSA

IEC

RoHS conform Certifications CSA (Class No. 1437-01)

CSA (File No. 22086)

CE marking

UL489

CSA certified

UL (File No. E140305)

UL listed

UL (Category Control Number DIHS)

IEC60947

CSA-C22.2 No. 5-09 Product specifications

Type Special features Non-delayed disconnection of NZM circuit-breaker or N switch-disconnector when the control voltage sinks below 35 - 70% US.

For use with emergency-stop devices in connection with an emergency-stop button.

When the under-voltage trip is switched off, accidental contact with the circuit breaker's primary contacts is prevented when switched on.

Undervoltage releases cannot be installed simultaneously with NZM...-XHIV... early-make auxiliary contact or NZM...-XA... shunt release.

10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM2/3-XU380-440AC with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.