

INDUSTRIAL COMPONENT DATA

NZM4-XU48DC 266205 Y7-266205 EATON ELECTRIC

Undervoltage release, 48 V DC

Brand: EATON - MOELLER | Manufacturer Part Number: NZM4-XU48DC



Manufacturer	EATON - MOELLER
MPN / Reference	NZM4-XU48DC
Catalog number	Y7-266205
Category	Under voltage coil
Minimum order	1 Pcs
Document ID	EO-A4A8375148
Generated	2026-08-01

Product Overview

Undervoltage release, 48 V DC

NZM4-XU48DC

Eaton Moeller series NZM - Molded Case Circuit Breaker. Undervoltage release, 48 V DC, 4

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: non-delayed disconnection of NZM circuit-breaker or N switch-disconnector when the control voltage sinks below 35-70% US. For use with Emergency-Stop devices in conjunction with emergency-stop button. when the undervoltage release is de-energized, accidental contact with the main contacts of the switch during attempts to switch on is safely prevented . Undervoltage releases cannot be installed simultaneously with NZM..-XHIV.. early-make auxiliary contact or NZM..-XA.. shunt release. Can be used for: NZM4(-4), N4(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM release Catalog Number 266205 Model Code NZM4-XU48DC EAN

4015082662059 Product Length/Depth 107 mm Product Height 51 mm Product Width 64 mm Product Weight 0.218 kg

Compliances UL/CSA

IEC

RoHS conform Certifications UL (File No. E140305)

CE marking

IEC60947

CSA (Class No. 1437-01)

CSA certified

CSA-C22.2 No. 5-09

UL489

UL listed

CSA (File No. 22086)

UL (Category Control Number DIHS) Product specifications

Used with NZM4(-4), N4(-4) Type Accessory Undervoltage release Special features Non-delayed disconnection of NZM circuit-breaker or N switch-disconnector when the control voltage sinks below 35 - 70% US. For use with emergency-stop devices in connection with an emergency-stop button. When the under-voltage trip is switched off, accidental contact with the circuit breaker's primary contacts is prevented when switched on. Undervoltage releases cannot be installed simultaneously with NZM...-XHIV... early-make auxiliary contact or NZM...-XA... shunt release. 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provide...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM4-XU48DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.