

INDUSTRIAL COMPONENT DATA

+IZMX-UVR48DC 123747 EATON ELECTRIC Undervoltage release 48 VDC

Brand: EATON - MOELLER | Manufacturer Part Number: +IZMX-UVR48DC



Manufacturer	EATON - MOELLER
MPN / Reference	+IZMX-UVR48DC
Catalog number	123747
Category	Under voltage coil
Minimum order	1 Pcs
Document ID	EO-E3B78793E3
Generated	2026-08-03

Product Overview

Undervoltage release 48 VDC

Suitable for remote switching off, can be combined only with an undervoltage release

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER

Additional Product Information

Under Undervoltage release;48VDC Suitable for remote switching off, can be combined only with an undervoltage release [Delivery program

Product range Accessories Accessories Remote switching Accessories Undervoltage release Cannot be combined with a second shunt release. Maximum operating frequency [Actuations/minute] 3 Limited to 3/min due to the high pick-up current for 35 ms.

Please note - the circuit-breaker's switching frequency = 60/h Rated control voltage [Us] 48 V DC V Operating range [x US] 0,85 - 1,1 Factor max. holding current [In] 0.089 A max. pick-up current (35ms) [In] 16 A max. continuous power [AC/DC] 5 VA/W max. pull-in power (35ms) [AC/DC] 850 VA/W Circuit-breaker total switching time [@ US=100%] 37 ms For use with IZMX16..., IZMX40...

INX16..., INX40... Notes Can be continuously ON (100% DF)

, Design verification as per IEC/EN 61439

Operating ambient temperature min. -25 °C Operating ambient temperature max. +70 °C , Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Under voltage coil (EC001022) Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Undervoltage trip ()

[AKF015013]) Rated control supply voltage Us at AC 50HZ 0 - 0 V Rated control supply voltage Us at AC 60HZ 0 - 0 V
Rated control supply voltage Us at DC 48 - 48 V Voltage type for actuating DC Voltage type for actuating DC Type of
electric connection Flat plug-in connection Number of...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZMX-UVR48DC with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.