

INDUSTRIAL COMPONENT DATA

IZMX-UVR48DC 123748 0004357376 EATON ELECTRIC

Undervoltage release 48 VDC

Brand: EATON - MOELLER | Manufacturer Part Number: IZMX-UVR48DC



Manufacturer	EATON - MOELLER
MPN / Reference	IZMX-UVR48DC
Catalog number	0004357376
Category	Under voltage coil
Minimum order	1 Pcs
Document ID	EO-A54F118CC1
Generated	2026-07-31

Product Overview

Undervoltage release 48 VDC

IZMX-UVR48DC

Suitable for remote switching off, can be combined only with an undervoltage release

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers IZM**

Additional Product Information

EL-Nummer (Norway)0004357376Undervoltage release 48 VDCSuitable for remote switching off, can be combined only with an undervoltage releaseDelivery program

Product rangeAccessoriesAccessoriesRemote switchingAccessoriesUndervoltage releaseCannot be combined with a second shunt release.

Retrofitting kit

Slot on the right on the adapter plate.Maximum operating frequency [Actuations/minute]3Limited to 3/min due to the high pick-up current for 35 ms.

Please note - the circuit-breaker's switching frequency = 60/hRated control voltage [Us]48 V DC VOperating range [x US]0,85 - 1,1 Factormax. holding current [In]0.089 Amax. pick-up current (35ms) [In]16 Amax. continuous power [AC/DC]5 VA/Wmax. pull-in power (35ms) [AC/DC]850 VA/WCircuit-breaker total switching time [@ US=100%]37 msFor use withIZMX16..., IZMX40...

INX16..., INX40...InstructionsAn additional control circuit terminal block is required for retrofitting.

For fixed mounting circuit-breakers?#156593 and withdrawable unit circuit-breakers ?#156590NotesCan be continuously

ON (100% DF)

Design verification as per IEC/EN 61439

Operating ambient temperature min.-25 °C Operating ambient temperature max.+70 °C Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Under voltage coil (EC001022) Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Undervoltage trip () [AKF015013]) Rated control supply voltage U_s at AC 50 Hz 0 - 0 V Rated...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IZMX-UVR48DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.